

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33, & 34

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford under contract No. 44 dated May 30, 1854. (DCSO records Vol. 15 Page(s) 6436)  
-----  
Set post for corner from which:  
A B.Oak, 14" dia. bears N.40°E. 370 lks. dist.  
Made a mound and drove in charred stake in the center as per instructions.

Gene Johnson - Oct. 1955 - C.S. File 42/32 & M 11-39  
-----  
Corner not found.

Raymond Brown, surveyed for Ireland. June 1998 - M129-5  
-----  
Set - 2½" x 36" galv. I.P. with 3" brass cap mkd:  
T 29 S R 5 W  
S 28 | S 27  
S 33 | S 34  
PLS 2391  
1998

New Accessories -  
15" Oak, bears N.16°42'W., 103.1 ft. mkd. "T29S R5W S28 BT"  
10" Oak, bears N.72°10'E., 74.7 ft. mkd. "T29S R5W S27 BT"  
9" Oak, bears S.17°33'W., 10.0 ft. mkd. "T29S R5W S33 BT"  
8" Oak, bears S.28°43'E., 135.4 ft. mkd. T29S R5W S34 BT"

Note - Section corner was set using a retracement of DLC line notes from G.L.O. survey for Claim No. 41.

Found OK by J. Hibbs, Jan. 2001 - Vol. 20 Pg. 37 A&B  
Fd. BC - Dave Beedle, 2/9/2009 - M158-65