

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Pages 6437 & 6438)

Set a post for 1/4 sec. cor. from which,
A Black Oak, 4" dia., bears N.48°E., 19 lks.
A Laurel, 6" dia., bears S.35°W., 35 lks.

A.R. Evans - Feb. 1953 - C.S. File 41/135 - M 8-70

Set by prop. meas.
Set - 5/8" I.R.
18" B.O. N.30°E., 11.9'. Mkd: 1/4 S22 BT
14" Fir., N.26 1/2°W., 19.1. Mkd: 1/4 S21 BT

Doug. County Surveyors Office - James W. Byron, Deputy - Dale McFarland & John Powell - Feb. 1962 - C.S. File 49/64-61

Found - 5/8" I.R. at corner & both BTs as recorded by Evans.
NE BT, now snag, shows good scribing "1/4 S22 BT"
NW BT now stump.
Set - Brass Cap alongside I.R. & mkd: County Surveyor's Office, 1962 1/4 S21|22 T29S R5W.
New BTs -9" R. Fir, bears N.80°W., 27.0' scribed 1/4 S21 CS BT.
11" Laurel bears N.87 1/2°E., 36.8' scribed 1/4 S22 CS BT