

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Cor. Secs 15, 16, 21, & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6438)

Set a post for cor. to secs. 15, 16, 21, & 22; from which,
A pine, 8" dia., bears N.85°W., 160 lks.
A pine, 10" dia., bears S.5°W., 75 lks.
A B. Oak, 10" dia., bears S.45°E., 325 lks.
A R. Fir, 30" dia., bears N.18°E., 280 lks.

G.G. Stewart - Nov. 28, 1921 - Frank Drake - Jesse Davenport
- "Old" Cor. Book page 127 - Vol. 3 Page 104 - C.S. File 6/4

Found one BT. Others down or gone. I set 3/4" Iron pipe for corner. Marked new BTs
A 6" Fir, bears N.78°W., 30.0'.
A 12" Fir, bears S.86°E., 31.0'.
A 12" Pine bears S.5°W., 49.5'.
No other trees available.

CORNER REPORT ONLY

A.R. Evans - Sept. 1954 - For: City of Myrtle Creek - C.S.
File 41/300 - M 8-75

Found - 3/4" iron pipe with elbow.
12" Fir, S.86°E., 31.0' (down)
Fir, N.78°W., 30.0' (cut out)
12" pine, S.5°W., 49.5' (dead)

Doug. County Surveyors Office - James W. Byron, Co. Surveyor
- Dale McFarland - John Powell - March 1962 - C.S. 49/64-77

Found - 3/4" I.P. at Corner.
6" now 19" R. Fir, N.78°W., 30.0', face opened, pitched over.
12", now 24" Fir stump S.86°E., 31.0', shows scar.
12", now 16" pine, S.5°W., 49.5', opened, center rotted & burned, shows faint scribing.

New BTs - Rescribe now 19" R. Fir, N.78°W., S16 CS BT
30" Dbl. R. Fir, N.30°E., 8.4' scribed S15 T29S R5W CS BT.
16" R. Fir, bears S.59½°W., 50.2', scribed S21 T29S R5W CS BT.
15" R. Fir, bears S.28°E., 114.5', scribed S22 T29S R5W CS BT.

Set - Brass Cap alongside Corner pipe & Mkd: County Surveyor's Office, 1962

S 16	S 15
S 21	S 22

T 29 S