

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6438)

Set a post for ¼ sec. cor. from which,
A laurel, 3" dia., bears N.65°W., 8 lks.
A R. fir, 24" dia., bears N.75°E., 294 lks.

John H. Markham - For: Earl Stonerod - Witness: Earl Stonerod
- Oct. 9, 1953 - C.S. File 41/198

Determined by single proportional measurement.
At midpoint on section line set 1"x30" iron pipe, from which:
A 16" Fir, bears S.51°W., 8.3' mkd. ¼ S16 BT
A 18" Fir, bears N.35°E., 15.1' mkd. ¼ S15 BT.
Corner lies on N.E. slope approx. 400' East of Ridge.
Section corners lie N. 2214.3' and S. 2214.3'.

A.R. Evans - For: City of Myrtle Creek - Sept. 1954 - C.S.
File 41/300 - M 8-75

Found - 1" I.P. and 2 BTs mkd: ¼ S15 ¼ S16
N.40°22'E., 31.7' from true corner position
Recorded in Co. Surveyor's Office as set by J.H.
Markham, Jr.
Set by proportionalte meas. the following:
Set - 7/8" iron rod, blaze and scribe 2 BTs
18" Fir, N.63½°W. 38.2' mkd: ¼ S16 BT (Cop. tag
2741)
12" Fir, N.26½°E., 22.9' mkd: ¼ S15 BT (Cop. tag
2741)
(Dist. to center of trees)