

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 16

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6438)

Set a post for cor. to secs. 9, 10, 15, & 16, from which:
A B. Oak, 18" dia., bears S.55°E., 8 lks.
A B. Oak, 14" dia., bears N.5°E., 50 lks.
A B. Oak, 12" dia., bears N.43°W., 33 lks.
A B. Oak, 24" dia., bears S.63°W., 40 lks.

Doug. County Surveyors Office - Frank Cain, Deputy -Jan. 1920
- "Old" Corner Book Page 125 - FB 107 Page 13

Re-established from which:
A 12" Fir bears N.62°35'E., 59 lks.

Doug. County Surveyors Office - Ben B. Irving, Co. Surveyor
-Witness: R. Carey - C.S. File 38/28

Set - Oak Stake 4"x4"x3'
12" Fir, S.35°E., 36'.
30" Fir, S.80°W., 22.3'.
14" Fir, N.75°W., 63.8'.
12" Fir, N.75°E., 43.5'

A.R. Evans - For: The City of Myrtle Creek - Sept. 1954 -
C.S. File 41/300 - M 8-75

Found - 4"x4"x36" oak stake;
1" I.P. 3.0' from true corner position.
Set - Iron pipe in correct location from 4 O.B.T.s
12" Fir, S.35°E., 36.0'.
30" Fir, S.80°W., 22.3'. (Correct Dist. 21.3') (Cop.
tag RE 2741)
14" Fir, N.75°W., 63.8'.
12" Fir, N.75°E., 43.5'. (Correct Dist. 42.5') (Cop.
Tag, RE 2741)
(Distances to face)

Found 1" IP and 6 BTs by Mark Smalley, L.S. #2354 - For:
Roseburg Forest Products Co. - July/Sept 1993 - M 119-2