

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6424)  
-----  
Set ¼ sec. post at proper distance, from which,  
    A B. Oak, 10" dia., bears S.33°W., 48 lks.  
    A B. Oak, 12" dia., bears N.29°W., 63 lks.

John H. Markham, Jr., Engineer - Witnesses: Geo. & Wm Vaughn  
- April 22, 1951 - C.S. File 40/259-6  
-----  
At midpoint on township line set 1"x30" iron pipe, from which  
    A Fir 6" dia., bears N.32°W., 9.0' dist. mkd ¼ S34 BT.

B.L.M. Resurvey By Lynn M. Roseberry & James E. Jelley under  
Group #662. Surveyed Oct. 1967/June 1969. (DCSO records, Vol.  
38 Page 15517.)  
-----  
CORNER REPORT ONLY  
Point for the ¼ sec. cor. of sec. 34 only, at proportionate  
distance; there is no remaining evidence of the original  
corner. No permanent monument established.