

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6437)

Set ¼ sec. post at average dist., from which,
An alder, 12" dia., bears S.20°E., 44 lks.
An alder, 14" dia., bears N.25°W., 14 lks.

Frank Cain - 1911 - FB 55 PG 54 - "Old" Corner Book PG 128

Renewed by running between secs. 22 & 27 remarked 2 new trees
An Ash 24" dia., N.24°30'E., 32.6'
An Alder 12" dia., S.42°W. (32.6' ?)

Geo. J. Wenderoth - Feb. 1944 - (Could find no record source)

Found 24" Ash stump N.24°30'E., 32.6'. Badly decayed but scribe marks still showing. Marked by Frank Cain, January 24, 1911 (FB 55 PG 54).
Set ½" Gal. I. Pipe for corner.
Take for witness point South end of concrete pier on East side of North Myrtle Creek, S.85°11'W., 32.0'.
North end of the above pier N.52°23'W., 38.2'.