

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6438)

Set 1/4 sec. post at average dist., from which,
A B. Oak, 10" dia., bears N.30°W., 22 lks.
A B. Oak, 10" dia., bears S.12°W., 64 lks.

A.R. Evans - Feb. 1953 - C.S. File 41/135 - M 8-70

Set by prop. meas.
Set - 3/4" I.R.
16" Fir, N.32°E., 1.8'. Mkd: ¼ S15 BT
10" Fir, S.58°W., 37.2'. Mkd: ¼ S22 BT
Both have copper tags mkd: R.E. 2741 nailed on.

CORNER REPORT ONLY

A.R. Evans - For: City of Myrtle Creek - Sept. 1954 - C.S. File 41/300

Found - 3/4" iron rod and 2 BTs
16" Fir, N.32°E., 1.8'.
10" Fir, S.58°W., 37.2'.

Doug. County Surveyors Office - James W. Byron, Deputy - Dale McFarland - John Powell - Feb. 1962 - C.S. File 49/64-65

Found - 3/4" I.R. at corner and both BTs as recorded by Evans, except now 12" Firs bears S.52°W., not S.58°W.

N.E. BT now stump, shows scribing.
Set - Brass cap alongside 3/4" I.R. & mkd:
County Surveyor's ¼ $\frac{S\ 15}{S\ 22}$ T29S R5W
Office, 1962

New BT - 18" Cedar bears N.26°W., 44.0' scribed ¼ S15 CS BT
Note - 4 Way fence corner & 1½" I.P. bears S.28°W., 74'.