

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6439)

Set ¼ sec. post at cor. average dist. from which:
A B Oak, 10" dia., bears S.27°W., 110 lks.
A B Oak, 14" dia., bears N.82°E., 163 lks.

Doug. County Surveyors Office - Ben B Irving, Co. Surveyor -
Witness: R. Carey - May 1945 - C.S. File 38/28

Set - 8x10x20" Serpentine Rock 10" in ground and mound of
stone marked ¼ on face.
8 " Oak, N. 64 ° E . , 1 3 6 ' .
12" Oak, S.70°E., 119.6'.
Set by proportionate dist. between Sec. Corners.

A.R. Evans - For: The City of Myrtle Creek - Witness: Milo
Godfrey - Sept. 1954 - C.S. File 41/300 - M 8-75

Set - 3/4" iron pipe in mound of rock from 2 O.B.T.s
Found - 8" W. O. N.64°E., 136.0'. (Copper tag RE 2741)
12" W. O. S.70°E., 119.6'. (Copper tag RE 2741)
Both O.B.T.s alive and in good condition.
New BT - 14" Alder S.4½°W., 97.8', Mkd: ¼ S15 BT. Cop. tag, RE
2741
Measured to center of tree
On all 3 trees placed copper tag - RE 2741

Doug. County Surveyors Office - Randall Smith, Deputy -
Terrie Franssen - March 29, 1991 - C.S. File 64/13-16

Found - 12" now 15" dia., Oak with a fully healed single
blaze. We open and found scribing "S15" bears
S.70°E. 119.6' (distance is good to center of
trunk and face of blaze)
No other BTs or monument found
Set - A 5/8"x30" long iron rod with a DCSO alum. cap, is
set 1" below road surface. Iron rod set at record
bearing and dist. to 1945 renewals southeast BT.
(N.70°W., 119.6')
New Accessories:
A 5/8"x30" I.R. with a DCSO alum. cap stamped "BO 1
1991" protrudes 2" above ground, bears N.47°E.,
53.67'.
A found 5/8" I.R. protruding 6" above ground bears
S.77½°E., 50.14'
A found 5/8" I.R. protruding 2" above ground bears
N.31°W., 35.38'