

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6440)

Set 1/4 sec. post at average dist., from which
A B. Oak, 20" dia., bears S.27°W., 75 lks.
A B. Oak, 8" dia., bears N.47°E., 125 lks.

George J. Wenderoth - 1957 - M 5-38

Corner set by proportional measurement, (halfway between sec. corners)
Set - 3/4" iron pipe, from which
12" Cedar, S.68°48'W., 21.0'.
12" Cedar, S.2°22'E., 55.8'.

Doug. County Surveyors Office - Gary Langlitz - P. Earle - 12/12/73 - C.S. File 56/41-2

Found - 3/4" iron pipe.
12" Incense cedar snag, down, bears S.69°W., 21.4' (rec. S.68°48'W., 21.0') We remove soil from scribe area and find scribing "1/4"
12" Fir stump bears S.3°E., 55.8'. (record 12" cedar, S.2°22'E., 55.8') Scribing "1/4 BT" visible.
Set - Brass cap mkd: County Surveyors T 29 S
Office 1/4 S 3
1973 S10
R 5 W WM
With 3/4" I.P. alongside from which I mark new BTs;
22" D. Fir, bears N.70°W., 125.7' scribed 1/4 S3 CS BT
18" D. Fir, bears N.14 1/2°W., 88.7' scribed 1/4 S3 CS BT

Mark Smalley, L.S. #2354 - For: Roseburg Forest Products Co. - July/Sept 1993 - M 119-2

Found - 1973 County Surveyor BCIP & 3/4" IP
BTs - 30" Fir, N.70°W., 125.7', healed.
24" Fir, N.15°W., 88.7', healed.
12" Fir, S.2°E., 55.8', rotten stump.
THIS MONUMENT BEARS N.38°52'58"W., 12.24', FROM THE POSITION CALCULATED FOR THIS CORNER.

Michael Erickson & Leonides Sandoval - For: Ensite USA - 9/2019 - M171-73A-D

Found - 2 1/2" Co. Surveyor brass cap dated 1973
Set - 9.5" Pine scribed "BT" N.32°E. 7.8' to nail side center
11.5" Fir scribed "BT" N.30°E., 55.5' to nail side center