

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION Cor. Secs 34 & 35 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6424)

Set a post at proper dist. for cor. to secs. 2, 3, 34, & 35, from which,

- A W. Oak, 6" dia., bears S.80°W., 9 lks.
- A W. Oak, 8" dia., bears S.15°E., 60 lks.
- A W. Oak, 6" dia., bears N.80°W., 9 lks.
- A Laurel, 14" dia., bears N.45°E., 170 lks.

G.L.O. Survey by Oscar F. Thiel, under Contract #658 dated May 21, 1896. (DCSO records Vol. 17 Page 7172)

Found a post, 4" sq. 24" above ground, marked and witnessed as described by the surveyor general, the NE witness tree, a laurel, 18" dia., is the only one left, a fire has burnt all the timber.

John H. Markham, Jr., Engineer - Witness: Wm. Markham - March 29, 1951 - C.S. File 40/259-7

Determined by O.B.T.
A Laurel, 20" dia., bears N.45°E., 103.0' dist. O.B.T.
At corner point set 1"x24" iron pipe, from which
A Fir, 8" dia., bears N.64°E., 17.0' dist. mkd. S35 BT.
A Laurel, 10" dia. bears N.24°W. 19.0' dist. mkd. S34 T29S, R5W, BT.

B.L.M. Resurvey By Irving Zirpel, Jr., under Group #355. Surveyed July 1957/Sept. 1957. (DCSO records Vol. 28 Pages 12113 & 12114)

Section corner determined at record bearing & distance from the only remaining bearing tree, as follows:

A madrone, 23" dia., bears N.45°E., 170 lks. dist., with rotted center, no scribe marks visible.

At the corner point

Set an iron post, 30" long, 2" dia., 18" in the ground to bed rock, with brass cap marked:

T29S R5W
S 34 | S 35
T30S R5W
S 3
1957

from which

A fir, 12" dia., bears N.22°E., 22 lks. dis., marked T29S R5W S35 BT.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Cor. Secs 34 & 35 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 13" dia., bears N.74½°W., 35½ lks dis., marked T29S R5W S34 BT.
 From this point a locally established and recorded cor. bears N.45°E., 22 lks. dist., monumented with an iron post, 1" dia., 12" above ground, from which,
 A locally established BT, a turned-out fir, 12" dia., bears N.50°E., 39 lks. dist., with illegible scribe marks visible on a partially healed blaze.
 A locally established BT, a madrone, 11" dia., bears N.9½°W., 38 lks. dist., bark scribed S34 T29S R5W BT.

B.L.M. Resurvey By Lynn M. Roseberry & James E. Jelley, under Group #662. Surveyed Oct. 1967/June 1969. (DCSO records Vol. 38 Page 15516)

 The cor. of secs. 34 & 35 only, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass cap mkd:
 T 29 S R 5 W
 S 34 | S 35
 T 30 S R 5 W
 S 3
 1957

from which the remains of the original bearing trees
 A madrone, 24" dia., bears N.45°E., 170 lks. dist., no marks visible on decayed blaze.
 and the remains of bearing trees mkd. by Zirpel
 A fir, 13" dia., bears N.22°E. 22 lks. dist., with healed blaze.
 A root hole, bears N.74½°W., 35½ lks. dist., with a down fir alongside, 14" dia., with healed blaze.
 from which a new bearing tree
 A cedar, 11" dia., bears N.2°W., 33 lks. dist., mkd. T29S R5W S34 BT.
 From this point, a local corner, established by John H. Markham, Jr., Registered Engineer No. 2880, in 1951, bears N.45°E., 0.22 chs. dist., monumented with an iron pipe, 1" dia., firmly set, projecting 12" above ground, from which the remains of bearing trees mkd. by Markham:
 A root hole, bears N.50°E., 39 lks. dist., with a down fir alongside, 12" dia., with illegible scribe marks visible on partially healed blaze.
 A madrone, 12" dia., bears N.9½°W., 38 lks. dist., with scribe marks S34 T29S R5W BT visible on bark.

Fd. OK, Sept. 1990, Donald Bentz, M 110-61

continued next page

2

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION Cor. Secs 34 & 35 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

DCS0-GIS Corner visitation - 3/11/2004 - Typed: 2/1/2011 -
C.S. File 67/33-1

Monument - GLO/BLM BC/IP - 2.5"
Comment - OK

BLM dependent resurvey by Jeffrey O. Covington, Cadastral
Surveyor, under Group No. 2795, surveyed July/Aug. 2015-
(DCS0 records Vol. 59 Page 23567-8)

The cor. of secs. 34 & 35 only, on the S. bdy of the Tp.,
monumented with an iron post, 2½" dia., firmly set,
projecting 6" above ground, with brass cap (properly) mkd.
from which the remains of an original bearing tree reported
by Roseberry and Jelley in 1967-69

A root hole bears N.45°E., 112.2 ft., with madrone
regrowth now growing in its place.
and the remaining bearing tree mkd. by Zirpel in 1957 and
reported by Roseberry and Jelley

A fir, 22" dia., bears N.22°E., 14.5 ft., with a healed
blaze.

and the bearing tree mkd. by Roseberry and Jelley

A cedar, 18" dia., bears N.2°W., 21.8 ft., with a healed
blaze.

From this cor., a point established by Markham, in 1951,
bears N.46°07'30"E., 15.29 ft. (Record, N.45°E., 14.52 ft.),
monumented with an iron pipe, 1" dia., firmly set, projecting
12" above ground, from which the remains of a bearing tree
mkd. by Markham and reported by Roseberry and Jelley

A madrone, 19" dia., bears N.9½°W., 25.1 ft., with no
marks visible.