

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6432)

Set a post for ¼ sec. cor. from which , a lone
B. Oak 12" dia., bears S.79°E., 422 lks.
Made mound as per instructions.
There being no timber convenient.

Gene E. Johnson, R.E. No. 3561 - Oct. 1955 - C.S. File 42/32
- M 11-39

This corner set 14.5' west of the Southwest corner of the
Ireland D.L.C. No. 47 as is given in the original notes.

Doug. County Surveyors Office - James W. Byron & Crew - For:
Douglas Co. - March 1962 - M 23-35

Set from tie to S.W. Corner DLC No. 47 per gov't notes.
Set - Brass cap at cor. mkd:
¼ S27|26 T29S R5W County Surveyor's Office 1962
New BT - 13" B. Oak bears S.53°E., 153.6' scribed ¼ S26 CS BT

Fd B.C. 4/92 by J. Artman M 115-20
Fd. OK 7/95 by D.Bentz - M122-33 & M122-34
Fd. Ok by Ken Hoffine -May 2004 - M144-71 A&B