

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6432)

Set a post cor cor. to secs., 22, 23, 26, & 27; from which

- A B. Oak, 10" dia., bears N.87°E., 350 lks.
- A W. Oak, 6" dia., bears S.88°E., 340 lks.
- A W. Oak, 14" dia., bears S.12°W., 626 lks.
- A W. Oak, 12" dia., bears N.6°W., 350 lks.

Geo. J. Wenderoth - Feb. 1944 - (Could find no record source)

Found - 12" White Oak (now 26") N.6°W., 231.0'.
 Set - 3/4" Gal. I. pipe for corner. Marked 4 new witness trees.

- 16" White Oak S.39°00'W., 11.3'
- 16" White Oak N.74°38'W., 24.4'
- 10" White Oak N.38°32'E., 30.5'
- 12" White Oak S.63°16'E., 77.5'

B.L.M. Survey By Irving Zirpel, Jr. under Group #355. Surveyed July/Sept 1957 (DCSO records, Vol. 28 Page 12119)

The only remaining original bearing tree is as follows:
 A White Oak, 21" dia., bears N.6°W., 350 lks. dist., with illegible scribe marks visible on opened blaze.

At the corner point
 Set an iron post, 30" long, 2" dia., 28" in the ground and in a mound of stone, 2' base, 1' high, with brass cap marked

T29S	R5W
S 22 S 23	
S 27 S 26	
1957	

from which

- A white oak, 18" dia., bears N.58°E., 105½ lks. dist., marked T29S R5W S23 BT.
- A white oak, 12" dia., bears S.13°E., 151½ lks. dist., marked T29S R5W S26 BT.
- A white oak, 12½" dia., bears S.37°W., 77 lks. dist., marked T29S R5W S27 BT.
- A white oak, 15" dia., bears N.15½°W., 213 lks. dist., marked T29S R5W S22 BT.

From this corner a locally established cor. of secs. 22, 23, 26, & 27, bears N.6°W., 4 lks. dist., monumented with a 3/4" galvanized pipe, flush with the ground, from which locally established BTs.

- A white oak, 8" dia., bears N.38°E., 46 lks. dist., with healed blaze.

(Cont. Next Page)

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A white oak, 13" dia., bears S.53 3/4°E., 119 lks. dist., with a healed blaze.
E. Fork of a double white oak, 11" dia., bears S.42°W., 18 lks. dist., with a healed blaze.
A white oak, 18" dia., bears N.75¼°W., 38 lks. dist. with S22 CS visible on open blaze.
A white oak, 14" dia., bears N.45°E., 54 lks. dist., with NE DLC 45 S visible on open blaze.

Found Brass Cap & all BTs March 12, 1962, M 23-35.

Doug. County Surveyors Office - Larry Monrean - P.L. Earle - T.R. Plouff - Oct. 5, 1978 - C.S. File 60/17-12

Found - A 1957 Cadastral brass cap properly marked.
3/4" I.P. bears N.6°W., 3.08'
Orig. BT, a W. Oak 12" now 24" bears N.6°W., 231.5' (rec. 231.0') Single blaze has been previously opened to the heart of the tree.
A W. Oak, 18" bears N.58°E., 70.1' to center of base (Rec. 69.6) Tree has well healed single blaze.
A W. Oak, 12" now 15" bears S.13°W., 100'. Tree has partially healed single blaze.
A W. Oak, 12½" now 15" bears S.36°W., 51.4' to center of base. (Rec. S.37°W., 50.8') Tree has well healed single blaze.
A W. Oak, 15" now 18" bears N.15½°W., 140.6'. Tree has well healed single blaze.
No new monument or accessories set.

FD OK By G. Grubb, Dec. 1981, RM 3-52
FD OK By H. Northcraft, 10/91, 1992-0021
FD OK By J. Artman, 4/92, M 115-20
Fd. OK by W. Ruppert, June 2003 - M143-20
Fd. Ok by Ken Hoffine -May 2004 - M144-71 A&B
Fd. Ok by Ed Farr, 12/2005 - 2006-0006