

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Cor. Secs 14, 15, 22, & 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6433)

Set a post for cor. to secs. 14, 15, 22, & 23, from which
A W. Oak, 24" dia., bears N.87°E., 71 lks.
An alder 18" dia., bears S.30°E., 96 lks.
An alder, 8" dia., bears N.43°W., 137 lks.
An alder, 14" dia., bears S.75°W., 27 lks.

G.G. Stewart - Witnesses: B. Hargis & W.S. Crear - April 4, 1922 - "Old Cor. Book Page 127 - C.S. File 8/39

Set - Iron Pipe from Orig. BT.
Mkd - A 14" Alder S.30°E., 63.0' O.B.T.
A 6" White Oak S.68½°W., 58.8'
A 12" White Oak N.3°E., 117.0'
No other trees available.

A.R. Evans, Eng. - Witness: J.L. Clinton - Aug. 1951 - C.S. File 40/363-6

Found - 1¼" Iron pipe and 1 BT
6" White Oak (now 15") S.68½°W., 58.8'
Blazed and scribed new bearing trees
6" Ash S.35°E., 33.0' marked T.29, R.5, S.23, R.E. 2741, B.T.
10" Alder, N.70°W., 105.0', marked T.29, R.5, S.15, R.E. 2741, BT.

Doug. County Surveyors Office - James W. Byron, Co. Surveyor - J. Powell & Crew - For: Co. Rd. & Sproul - 12/9/68 - C.S. File 54/74

Found - 1¼" Iron Pipe at sec. cor.
15" W. Oak S.68°30'W., 58.8', B.T. scribe visible.
New BT - 6" Ash S.39°E., 2.9' mkd: T29S R5W S23 CS BT
No other good trees near corner.
Note - This corner lies 2.0' East of Fence Corner, Fences run north and west.

FD OK By G. Grubb, Dec. 1981, RM 3-52
FD OK by K. DeGroot, March 1995, M 121-67

(Cont. Next Page)

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Cor. Secs 14, 15, 22, & 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas County Surveyors Office - Randall Smith & Stephen
Flause - Jan. 8, 1997 - C.S. 64/71-3

Found- 1 1/4" I.D. Iron pipe flush with ground (1922 Stewart).
No OBT's Found
6" now 32" dia. W.Oak, with a fully healed blaze,
bears S.68 1/2°W., 58.8'.
No other Bt's Fd.

Mon Set- None: BC/IP not set as fence line and post's would
need removed.

New BTs- 9" dia. Ash, double blazed and scribed "T29S R5W S14
CS BT", bears N.25°E., 7.7'.
8" dia. Ash, double blazed and scribed "T29S R5W S23
CS BT", bears S.23°E., 9.4'.

Kristian DeGroot - For: Philip Johnson - Jan. 2014 - M167-18

Found - A 1 1/4" iron pipe by Stewart in 1922 per CS file 8/39,
perpetuated from orig. evidence no longer in
existence, firmly set flush with the ground, 0.3'
NW of a new 6" wood fence post, with fences N-E-W

From which the remains of a BT by Byron in 1968:
A 36" W.Oak stump bears record S.68°30'W., 58.8',
with lower portion of blaze.

And BTs by Smith & Flause in 1997:
A 11" Ash bears record N.25°E., 7.7', with scribe
mks visible on partial healed dbl blaze.
A 11" Ash bears record S.23°E., 9.4', with scribe
mks visible on partial healed dbl blaze

NAD 83 (2011) EPOCH 2010.00

Latitude: 43°02'30.68451"N Longitude: 123°15'57.14946"W