

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor. Secs 2, 3, 10, & 11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6435)

-----  
Set a post for cor. to secs. 2, 3, 10, & 11; from which,  
A W. Oak, 8" dia., bears S.4°W., 475 lks.  
A W. Oak, 4" dia., bears S.20°E., 33 lks.  
A B. Oak, 12" dia., bears N.30°E., 223 lks.  
A B. Oak, 10" dia., bears N.87½°W., 360 lks.

John H. Markham, Jr. - Witness: Geo. Vaughn - Aug. 1, 1950  
C.S. File 40/259-3

-----  
Determined from remains of original BT  
B. Oak, 12" dia., bears N.87½°E., 240', I rescribe.  
W. Oak 12" dia., bears S.20°E., 22' dist., I remark this  
original BT S11 2880 BT.  
At corner point fd. 5"x5"x5" stone, from which,  
A W. Oak, 12" dia., bears S.3°W. 345' dist mkd S10 2880 BT

George J. Wenderoth - 1957 - M 5-38

-----  
This corner previously renewed by Markham on Aug. 1, 1950 -  
Set - 3/4" iron pipe, from which:  
16" W. Oak, S.3°W., 345.0', (Marked by Markham in 1950)  
13" W. Oak, S.31°26'E., 22.5'  
16" Pine, N.30°13'W., 28.5'  
14" Pine, N.33°45'E., 38.2'

Doug. County Surveyors Office - James W. Byron, Deputy - Dale McFarland - John Powell - March 1962 - C.S. File 49/64-76

-----  
Found - 3/4" I.P. at corner & BTs, as recorded by Wenderoth, 1957, except N.W. & N.E. BTs, now dead, burned in 1961 fire.

Set - Brass cap alongside I.P. & mkd:  
County Surveyor's, Office 1962

S 3 | S 2  
S 10 | S 11      T29S R5W

New BT - 14" R. Fir, bears S.69½°W., 63.2' scribed S10 T29S R5W CS BT.

No other live trees near.

Found Brass cap & 4 BT's by Mark Smalley, L.S. #2354 - For: Roseburg Forest Products Co. - July/Sept 1993 - M 119-2.

continued next page

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor. Secs 2, 3, 10, & 11

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Kris DeGroot - 12/2010 - M157-36

-----  
Lat: 43°04'12.340698" N Long: 123°15'54.558687" W.  
Found a 1¼" iron post by J. Byron in 1962 per C.S. 49/64,  
firmly set, projecting 6" above the ground, with a 2½" brass  
cap (Properly) marked  
From which an original bearing tree:  
A 15" W.Oak bears S.25¼°E., 21.8 ft with a high healed  
blaze & a low opened blaze. (Rec. S.20°E., 33 lks) 1962  
A root hole bears S.3¾°W., 341.8 ft with a uprooted 18"  
Oak alongside. (Rec. S.3°W., 345.0') And bearing trees  
by Wenderoth in 1957 per M5-38:  
A 16" W.Oak bears S.34°E., 22.6 ft with a healed double  
blaze. (Rec. S.31°26'E., 22.5 feet)  
A 24" Pine bears N.32¾°W., 28.3 ft with scribe marks "BT"  
visible on a partially healed double blaze. (Rec.  
N.30°13'W., 28.5 ft)  
A 27" Pine bears N.32¾°E., 37.5 ft with a healed double  
blaze. (Rec. N.33°45'E., 38.2 ft)  
And a bearing tree by Byron in 1962 per CS 49/64:  
A 35" R.Fir bears S.68½°W., 63.3 ft with a healed blaze.  
(Rec. S.69½°W., 63.2 ft)

Michael Erickson & Leonides Sandoval - For: Ensite USA -  
9/2019 - M171-73A-D

-----  
Found - 2½" Co. Surveyor brass cap dated 1962  
29" Pine w/visible scribing N.32°W., 28.5' to face  
30" Pine with healed blaze N.32°E., 37.5'  
37" Fir with healed face S.68°W., 63.3'  
16.5" Oak with healed face S25°E., 21.8'