

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 506100

PRIMARY CORNER DESCRIPTION Cor. Secs 2 & 3 T30-5 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6424)

Set a post at proper dist. for cor. to secs. 2, 3, 34, & 35, from which,

- A W. Oak, 6" dia., bears S.80°W., 9 lks.
- A W. Oak, 8" dia., bears S.15°E., 60 lks.
- A W. Oak, 6" dia., bears N.80°W., 9 lks.
- A Laurel, 14" dia., bears N.45°E., 170 lks .

G.L.O. Survey by Oscar F. Thiel, under Contract #658 dated May 21, 1896. (DCSO records Vol. 17 Page 7172)

Intersect N. bdy of Township, 5.65 E. of the cor. of secs. 2, 3, 34, & 35., which is a post, 4" sq. 24" above ground, marked and witnessed as described by the surveyor general, the NE witness tree, a laurel, 18" dia., is the only one left, a fire has burnt all the timber, I set a basaltstone 14x8x6 ins. 10 ins. in the ground for closing corner of secs. 2 & 3, marked C C on S, with 2 grooves on E. and 4 grooves on W. faces and raised a mound of stone, 2' base, 1½' high, S. of cor.

John H. Markham, Jr., Engineer - Witnesses: Geo. & Wm Vaughn April 22, 1951 - For:Hausteder Lbr.Co. - C.S.File 40/250A-7

At corner point drove 1"x30" truck axle in original stone monument, from which,
A Fir, 5" dia. bears S.87°E. 23.2', mkd. S2 T30S R5W BT.
An Oak, 6" dia. bears S.29°W. 18.7', mkd. S3 2800 BT.

B.L.M. Resurvey By Lynn M. Roseberry & James E. Jelley, under Group #662. Surveyed Oct. 1967/June 1969. (DCSO records Vol. 38 Pages 15534 & 15535)

Point for closing cor. of secs. 2 & 3.
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

T 29 S R 5 W
S 35
S 3 | S 2
C C
T 30 S R 5 W
1969

from which

(Cont. Next Page)

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 506100

PRIMARY CORNER DESCRIPTION Cor. Secs 2 & 3 T30-5 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 16" dia., bears S.62°E., 40½ lks. dist., mkd. T30S
R5W S2 CC BT.

A fir, 16" dia., bears S.40½°W., 108 lks. dist., mkd. T30S
R5W S3 CC BT.

From this point, the original closing cor. of secs. 2 & 3, bears N.0°08'W., 0.185 chs. dist., perpetuated and recorded by John H. Markham, Jr., Registered Engineer No. 2880, in 1951, from original evidence no longer in existence, monumented with an axle, 1" dia., firmly set, projecting 2' above ground, and in a mound of stone, 2' base, 1' high, from which the remains of bearing trees mkd. by Markham:

A fir stump, 8" dia., bears S.87°E., 35 lks. dist., with a down fir alongside, 8" dia., with scribe marks C BT visible on open blaze.

A root hole, bears S.29°W., 28½ lks. dist., with a down oak alongside, 6" dia., no marks visible.

From this same point, the cor. of secs. 34 & 35 only, T. 29 S., R. 5 W., bears S.89°37'W., 5.58 chs. dist.

DCS0-GIS Corner visitation - 3/11/2004 - Typed: 2/8/2011 -
C.S. File 67/33-1

Monument - 2½" IP/BC Comment - OK