

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 35

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6432)

Set 1/4 sec. post at average dist., from which,
 A B. Oak, 10" dia., bears N.50°E., 40 lks.
 A W. Oak, 8" dia., bears S.5°W., 26 lks.

Doug. County Surveyors Office - James W. Byron, County Surveyor - John Powell & Crew - April 1969 - C.S. File 54/84 - M 37-44

This corner set from survey at prorated distance.
 Set - Brass cap at cor. mkd:

County Surveyor's	T 29 S	R 5 W
Office	1/4 S 26	
	S 35	

New BTs -13" Maple, S.66°E., 110.6' mkd: "1/4 S35 CS BT"
 13" D. Fir, N.45°W., 84.2' mkd: "1/4 S26 CS BT"

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 5/9/2000 - C.S. File 66/16-1A

Found - 1969 BC/IP not found, falls in cat road.
 13" now 15" dia. Maple with a partially healed double blaze, illegible scribing visible bears S.67°E., 110.6 ft. (Rec. S.66° 110.6 ft.) 1969
 13" now 19" dia., D.Fir with a fully healed double blaze, bears N.46°W., 84.2 ft. (Rec. N.45°W., 84.2 ft.) 1969
 Set - 2 3/8" dia., brass cap on a 1 3/8" O.D. by 32" long iron pipe is near middle of cat road protrudes 8" above ground, marked:

	T 29 S
	R 5 W
1/4	S 26
	S 35
	2000

DOUGLAS COUNTY SURVEYORS OFFICE

10" Maple double blazed & scribed
 "1/4 S26 CS BT" bears N.11°E., 15.2 ft.
 8" D.Fir double blazed & scribed "1/4 S35 CS BT" bears
 S.49 1/2°W., 31.0 ft.

Cont.

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2795, surveyed July/Aug. 2015- (DCSO records Vol. 59 Page 23574-5)

The ¼ sec. cor. of sec. 26 and 35, reestablished at proportionate measurement by Byron, in 1969, and perpetuated by Smith, in 2000; there is no remaining evidence of the original cor., and is accepted as a careful and faithful reestablishment of the cor., monumented with an iron post, 1¼" dia., firmly set, projecting 8" above ground, with brass cap (properly) mkd.

from which the bearing trees mkd. by Byron

A maple, 16" dia., bears S.67°E., 108.9 ft., with a healed double blaze.

A fir, 24" dia., bears N.46°W., 83.7 ft., with a healed double blaze.

and the bearing trees mkd. by Smith

A maple, 12" dia., bears N.10¼°E., 15.3 ft., with a healed double blaze.

A fir, 16" dia., bears S.50°W., 30.5 ft., with a healed double blaze.