

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 540640

PRIMARY CORNER DESCRIPTION Center 1/4 Corner Sec. 2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Raymond Brown, LS 2391 - For: Umpqua Youth, Inc. - Jan. 1994
- 1994-0021 A & B

Set - 2"x36" iron pipe with 3" brass cap attached, mkd:
"PLS 2391, T29S R5W C¼ S2 1994"
10" Fir, bears S.11°27'E., 49.2', mkd: "C¼ S2 BT"
8" Maple bears S.72°30'W., 23.8', mkd: "C¼ S2 BT"
9" Madrona bears N.26°59'W., 89.1', mkd: "C¼ S2 BT"
8" Oak bears N.54°04'E., 167.1', mkd: "C¼ S2 BT"

Per Harvey Christensen's survey M 128-14, Nov. 1997, the
center 1/4 corner set by Raymond Brown bears N.00°24'53"E.,
25.7 ft from Christensen's calculated position.

Michael Erickson & Leonides Sandoval - For: Ensite USA -
9/2019 - M171-73A-D

Found - 2½" brass cap "PLS 2391" dated 1994
48" Fir W/BLM tag N.29°E., - 53.2' to face
10" Oak open faced blaze "C1/2 S2" S.54°W., 167'
12" Maple with healed blaze N.72°E., 24.3'
27" Fir with healed blaze N.11°W., 49.0'