

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 560200

PRIMARY CORNER DESCRIPTION E 1/16 Sec. Cor. 26 & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - James W. Byron, Co. Surveyor -  
March/April 1969 - M37-44 & C.S. File 54/84

-----  
Set - Brass cap at 1/16 cor., mkd. COUNTY SURVEYORS OFFICE  
1969M T29S R5W E 1/16 S26/S35.

New - 28" D.Fir, S.66°W., 33.8', mkd: E 1/16 S35 CS BT.  
12" D.Fir, N.83°E., 29.9', mkd: E 1/16 S26 CS BT.

Douglas Co. Surveyors Office - Stephen J. Flause - Jon  
Everett (Land Dept) - Feb. 24, 2010 - C.S. File 67/31-13

-----  
Found - A 2½" dia., brass cap (properly marked) on an iron  
pipe firmly set and protruding approx. 15" above  
ground. Monument leans approx. 0.6 ft. northerly  
from plumb. (Measurements to accessories are  
taken from plumb position)

A 28" D.Fir now a dead 23" DBH approx. 35 ft. tall,  
D.Fir snag with a single bark blaze marked "E1/16  
S35 CS" (lower blaze with BT not seen) bears  
S.66°W., 33.8 ft. Dist. as per record.

A 12" D.Fir, now a 12" DBH, 6 ft. tall rotted fir  
stub with an unhealed upper blaze marked "E1/16  
S26 CS" and a rotted out lower blaze; bears  
N.81°E., 29.9 ft. distant (Rec. N.83°E., 29.9')

Reset - Monument is returned to plumb position.

New - A 9" DBH D.Fir scribed "E 1/16 S26 CS BT" on a  
double blaze; bears N.62½°E., 19.0 ft.

An 8" DBH Madrone, scribed "E 1/16 S35 CS BT"; bears  
S.55°E., 3.0 ft.

Note - Monument is in SW corner of older clear-cut on  
moderate North slope just east from substantial  
North running draw.

Compass decl. 16°E.