

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6426)

-----  
Set ¼ sec. post, from which  
A B. Oak, 10" dia., bears S.27°E., 30 lks.  
A B. Oak, 6" dia., bears N.37°W., 45 lks.

B.L.M. Survey By Irving Zirpe., Jr., under Group #355. Surveyed July/Sept. 1957 (DCSO records Vol. 28 Page 12114)

-----  
Point for the ¼ sec. cor. of secs. 35 & 36, at proportionate distances; there is no remaining evidence of the original corner.

Set an iron post, 30" long, 2" dia., 28" in the ground with brass cap marked:

T29S R5W  
          ¼  
          S 35 | S 36  
          1957

from which

A fir, 14" dia., bears N.54½°E., 341 lks. dist., marked ¼  
S36 BT  
A fir, 12" dia., bears S.50 3/4°W., 110 lks. dist., marked  
¼ S 35 BT.

Fd. Ok by Ken Hoffine -May 2004 - M144-71 A&B  
FD. Ok by Ken Hoffine, 1/2006 - M149-60

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2795, surveyed July/Aug. 2015- (DCSO records Vol. 59 Page 23570-1)

-----  
The ¼ sec. cor. of secs. 35 and 36, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd.

from which the bearing trees mkd. by Zirpel in 1957

A fir, 29" dia., bears N.54½°E., 225.1 ft., with a healed blaze.  
A fir, 24" dia., bears S.50¾°W., 72.6 ft., with a healed blaze.

Corner is located on an ENE slope.

From the corner

N., 18 ft., to shallow ravine, drains E.