

PRIMARY CORNER DESCRIPTION Cor. Sec.s 25, 26, 35 & 36

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6426)

Set a post, cor to secs. 25, 26, 35, & 36, from which
A Laurel, 16" dia., bears S.70°W., 72 lks.
A Laurel, 14" dia., bears S.10°E., 15 lks.
A Laurel, 18" dia., bears N.75°E., 25 lks.
A Laurel, 8" dia., bears N.20°W., 70 lks.

B.L.M. Survey By Irving Zirpel, Jr., under Group #355. Surveyed July/Sept. 1957 (DCSO records Vol. 28 Page 12115)

Point for cor. of secs. 25, 26, 35, & 36, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 30" long, 2" dia., 28" in the ground, with brass cap marked:

T29S R5W
S 26 S 25
S 35 S 36
1957

from which,

- A fir, 9" dia., bears N.72°E., 75½ lks. dist., marked T29S R5W S25 BT
- A fir, 11" dia. bears S.23°E., 53½ lks. dist., marked T29S R5W S36 BT
- A fir, 9" dia., bears S.76½°W., 62 lks. dist., marked T29S R5W S35 BT
- A madrone, 8" dia., bears N.7°W., 74 lks. dist., marked T29S R5W S26 BT

Doug. County Surveyors Office - James W. Byron, Co. Surveyor - John Powell & Crew - April, 1969 - C.S. File 54/84 - M 37-44

Found - BLM brass cap properly marked in 1957.

- 9" Fir, now 10" N.72°E., 49.5', pitched over scribe visible.
- 11" Fir, now 11" S.23°E., 35.0', pitched over scribe visible.
- 8" Laurel, now 9" N.7°W., 48.8', scribing visible, mostly grown over.
- 9" Fir, now snag, S.76½°W., 40.9', pitched over, scribe visible.

New BT - 10" Laurel S.33½°W., 66.6' mkd: T29S R5W S35 CS BT

This corner lies on top of large ridge, running north.