

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6427)

-----  
Set a post on top of ridge, for ¼ sec. cor., from which  
A Red Fir, 20" dia., bears N.30°W., 62 lks.  
A Red Fir, 15" dia., bears S.37°E., 43 lks.

B.L.M. Survey By L Irving Zirpel, Jr., under Group #355. Surveyed July/Sept. 1957 (DCSO records Vol. 28 Page 12118)

-----  
Point for the ¼ sec. cor. of secs. 25 & 26, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 30" long, 2" dia., 28" in the ground, with brass cap marked:

T29S R5W  
          ¼  
          S 26 | S 25  
          1957

from which

A fir, 17" dia., bears S.37¼°E., 38 lks., mkd ¼ S25 BT  
A fir, 20" dia., bears S.87 3/4°W., 36 lks., mkd ¼ S26 BT

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2795, surveyed July/Aug. 2015- (DCSO records Vol. 59 Page 23570-1)

-----  
The ¼ sec. cor. of secs. 25 and 26, monumented with an iron post, 2½" dia., firmly set, projecting 2" above ground, with brass cap (properly) mkd.

from which the bearing trees mkd. by Zirpel in 1957

A fir, 32" dia., bears S.37¼°E., 25.1 ft., with a healed blaze.

A fir, 32" dia., bears S.87¾°W., 23.8 ft., with a healed blaze.

NAD 1983 (2011)

Latitude: 43°01'10.982"N.      Longitude: 123°14'47.436"W.