

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor. Secs. 23, 24, 25, & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6427)

-----  
Set a post in South Myrtle Creek, for cor. to secs. 23, 24, 25, & 26, from which,  
An Alder, 12" dia., bears S.35°E., 40 lks.  
An Alder, 10" dia., bears N.20°E., 35 lks.  
An Alder, 8" dia., bears N.20°W., 31 lks.  
An Alder, 12" dia., bears S.65°W., 55 lks.

B.L.M. Survey By Irving Zirpel, Jr., under Group #355. Surveyed July/Sept 1957 (DCSO records Vol. 28 Pages 12118 & 12119)

-----  
Point for the cor. of secs. 23, 24, 25, & 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36" long, 2" dia., 12" below the surface of the ground, with brass cap marked:

T29S R5W
S 23   S 24
S 26   S 25
1957

from which  
A cottonwood, 14" dia., bears N.19°E., 152 lks. dist., marked T29S R5W S24 BT.  
A maple, 15" dia., bears S.88°E., 686 lks. dist., marked T29S R5W S25 BT.  
A maple, 15" dia., bears S.41¼°W., 299 lks. dist., marked T29S R5W S26 BT.  
A maple, 9" dia., bears N.14 3/4°W., 90 lks. dist., marked T29S R5W S23 BT.

Fd. Ok by Ken Hoffine -May 2004 - M144-71 A&B