TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6429)

Set a post for ¼ sec. cor., from which
A B. Oak, 12" dia., bears N.25°W., 47 lks.
A B. Oak, 10" dia., bears S.45°E., 60 lks.

Doug. County Surveyors Office - John M. Powell & Crew - C.S. File 49/64-84 - 10/15/71

Found - 12", now 30" B. Oak, N.25°W., 31.0', opened for scribing "B"
No trace of S.E. BT
Set - Brass cap at cor. mkd; County Surveyor's Office, 1971 T29S R5W ¼ S14 S13
New BTs -30" W. Oak, S.70°E., 48.7' scribed ¼ S13 CS BT
14" D. Fir, N.80°W., 24.0' scrived ¼ S14 CS BT

Fd OK by George Grubb, Dec. 1981, RM 3-52

K.DeGroot, Aug. 1998 - M129-11 survey for Bill Van Cleave

Found 1971 DCSO 1¼" IP with 2½" brass cap, bent over at ground level by logging operations. I referenced, removed, straightened and reset BCIP in its original position.