

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2, 11, & 12

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6430)</p> <p>-----</p> <p>Set a post, cor. to secs. 1, 2, 11, & 12, from which</p> <ul style="list-style-type: none">A B. Oak, 16" dia., bears S.88°E., 36 lks.A B. Oak, 16" dia., bears N.50°E., 75 lks.A Laurel, 14" dia., bears N.30°W., 53 lks.A B. Oak, 12" dia., bears S.85°W., 103 lks.
<p>Doug. County Surveyors Office - G.G. Stewart, Deputy - Witnesses: George Wixon & A.W. Yokum - Nov. 4, 1921 - F.B. 35 Page 40 - Vol. 3 Page 103 - "Old" Cor. Book Page 126</p> <p>-----</p> <p>I find three BTs, the fourth a Black Oak had fallen. Set a 4" square White Oak post for corner and mark a new B.T.</p> <ul style="list-style-type: none">A 18" Fir, N.90°W., 28 lks.
<p>Douglas Co. Surveyors Office - W. Penley & J. Heritage - Aug. 1970 - C.S. File 54/81</p> <p>-----</p> <p>Not Found. Corner lies in burnt logged off area. Had good line from old Oak tree with old "X" and line tag in reference to ¼ cor. 2 & 11. <u>Note:</u></p> <ul style="list-style-type: none">April 1972, 2nd search - no more evidence found. V.R.T. (C.S. 54/81)
<p>Douglas Co. Surveyors Office - Randall Smith, Stephen Flause; Oct. 14, 1996 - C.S. File 65/9-27</p> <p>-----</p> <p>Found - Recent BC/IP set by Harvey Christensen at proportioned position. (Unfiled at this time)</p> <p>Accessories Found -</p> <ul style="list-style-type: none">4 BT's scribed by Harvey Christensen for proportioned position. Bearings & distances of BT's not checked.A search for original BT's and renewal BT from 1921 was made. No evidence of BT's was found. <p>Note: This corner was searched for by DCSO in 1970 & 1972 and not found.</p>
<p>Harvey Christensen - For: McDougal Brothers & Rosboro Lumber Co. - Nov. 1997 - M 128-14</p> <p>-----</p> <p>Set - 1997 2½" BC on 2"x30" I.Pipe, ½ ft. above grade. MKD:</p> <ul style="list-style-type: none">NTCIT29S R5W<u>S2</u> <u>S1</u>S11 S12 <p>1997 PLS 2603 (Cont. next page)</p>

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2, 11, & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

3" P.Madrone N.31°W. 13.3 ft. blazed & scribed "X BT"
3" P.Madrone N.2°W. 19.4 ft. blazed & scribed "X BT"
3" P.Madrone N.49°W. 4.1 ft. blazed & scribed "X BT"
4" P.Madrone S.45°E., 6.2 ft. blazed & scribed "X BT"
5 ft. steel post 1 ft. North.

Kris DeGroot - 12/2010 - M157-36

Lat: 43°04'11.854361" N Long: 123°14'44.899053" W.
THE M128-14 BCIP BY H. CHRISTENSEN IN 1997 HAS BEEN DESTROYED BY A 100 FOOT X 200 FOOT WIDE LANDSLIDE. The monument is now laying on top of the ground. **All the M128-14 bearing trees are located within the slide area and have moved from their original positions.** The corner position is computed by double proportionate measurement.