

PRIMARY CORNER DESCRIPTION Cl. Cor. for Secs. 1 & 2 T30-5.

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6423)

-----  
Set a post for cor. to secs. 1, 2, 35, & 36, from which ,  
A Yellow Pine, 20" dia., bears S.30°E., 100 lks.  
A B. Oak, 10" dia., bears N.26°E., 42 lks.  
A Laurel, 20" dia., bears N.31°W., 100 lks.  
A B. Oak, 18" dia., bears S.27°W., 80 lks.

G.L.O. Survey by Oscar F. Thiel, under Contract #658 dated May 21, 1896 (DCSO records, Vol. 17 Page 7168)

-----  
Set a basalt stone, 14x10x6 ins. 10 ins. in the ground for closing cor. of secs. 1 and 2, marked C C on S; with 1 groove on E. and 5 grooves on W. faces, from which,  
A B. Oak, 10" dia., bears S.4°W., 108 lks. dist. mkd. T30S R5W S2 BT.  
No other trees within limits, raised a mound of stone 2' base, 1½' high, S. of cor. This cor. stands on NW slope in burnt laurel and oak underbrush.

B.L.M. Survey by Lynn M. Roseberry & James E. Jelley, under Group #662. Surveyed Oct. 1967/June 1969. (DCSO records Vol. 38 Pages 15513 & 15514)

-----  
Point for the closing cor. of secs. 1 & 2, T. 30 S., R. 5 W., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

T 29 S R 5 W  
S 36  
S 2 | S 1  
C C  
T 30 S R 5 W  
1969

from which

A Fir, 15" dia., bears S.32¼°E., 83 lks. dist., mkd. T30S R5W S1 CC BT.

A Fir, 12" dia., bears S.7¼°W., 130 lks. dist., mkd. T30S R5W S2 CC BT.

Doug. County Surveyors Office - Randall Smith, Deputy - Stephen Flause - Terrie Franssen - March 15, 1991 - C.S. File 64/13-9

-----  
Fnd - 3¼" dia., B.L.M. brass cap on 2½" O.D. I.P., protruding 7" above ground. BC/IP leans approx 3" NE of plumb. Cap stamped 1969. (Cont. Next Page)

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 606100

PRIMARY CORNER DESCRIPTION Cl. Cor. Sec. 1 & 2 T30-5

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

15" now 20" D. Fir with a fully healed single blaze,  
bears S.32¼°E., 54.8' (agrees with record)  
12" now 18" D. Fir with a fully healed single blaze,  
bears S.7¼°W., 85.8' (agrees with record)  
New BTs - 4" dia. D. Fir double blazed and scribed "XBT"  
bears S.2°E., 26.2'.  
11" dia. D. Fir double blazed and scribed "T30S  
R5W S1 CC CS BT", bears S.70°E., 71.7'.  
Note - Corner is along the north edge of a dirt road.

---

FD. Ok by Ken Hoffine, 1/2006 - M149-60

---

DCSO-GIS Corner visitation - 2/23/2006 - Typed: 2/1/2011 -  
C.S. File 67/33-1  
-----  
Monument - GLO/BLM - 3¼ BC/IP  
Comment - ok; 4 live BTs

---

2