

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6427)

Set ¼ sec. post at average distance, from which
A W. Oak, 8" dia., bears N.43°E., 125 lks.
A Pine, 8" dia., bears S.29°W., 70 lks.

B.L.M. Survey By Irving Zirpel, Jr., under Group #355. Surveyed July/Sept. 1957 (DCSO records Vol. 28 Page 12116)

Point for the ¼ sec. cor. of secs. 25 & 36, at proportionated distance; there is no remaining evidence of the original corner.

Set an iron post, 30" long, 2" dia., 28" in the ground, with brass cap mkd:

T 29 S
¼ S 25
 S 36
 1957

from which

A fir, 12" dia., bears N.18°W., 11½ lks. dist., mkd. ¼ S
25 BT

A fir, 12" dia., bears S.67°W., 88 lks. dist., mkd. ¼ S 36
BT

FD. Ok by Ken Hoffine, 1/2006 - M149-60