

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 24 & 25

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6428)

Set ¼ sec. post at average dist., from which
A B. Oak, 12" dia., bears N.75°E., 23 lks.
A B. Oak, 12" dia., bears S.15°W., 50 lks.

Doug. County Surveyors Office - H.L. Eppstein, Co. Surveyor -W.S. Crear - March 13, 1928 - "Old" Corner Book Page 127 - C.S. File 6/53 - C.S. File 8/39

Set corner from old BT:
A 12" Black Oak, N.75°E., 23 lks. Scribe marks plain for BT. Other tree gone.
Set - 3"x3"x3' Cedar post and marked new B.T.s
12" Cedar N.5°W., 87 lks.
10" Fir N.74°E., 63 lks.

Doug. County Surveyors Office - James Byron - Ray Irving - Dec. 11, 1953 - C.S. File 45/231

Corner positively identified from stumps of old BTs.
12" cedar N.5°W., 87 lks.
10" fir N.74°E., 63 lks. Scribing still legible.
Set - 3/4" iron rod and blazed and scribed two new trees.
10" Red fir, N.85°W., 46.5' dist. mkd ¼ S24 CS BT
12" R. Fir, N.55°E., 40.0' fist. mkd ¼ S 24 CS BT

B.L.M. Survey By Irving Zirpel, Jr., under Group #355. Surveyed July/Sept. 1957 (DCSO records Vol. 28 Page 12120)

The ¼ sec. cor. of secs. 24 & 25 perpetuated by an iron rod, 3/4" dia., 6" above ground, firmly set. This cor. was restored from the original bearing trees, which are no longer in existence, Eppstein, County Surveyor, in 1938 and rehabilitated by Byron and Irving, Deputy County Surveyors, in 1953; from which the locally established bearing trees, as follows:

A fir, 15" dia., bears N.58°E., 60½ lks. dist., marked with a partially healed blaze.
A fir, 15" dia., bears N.85°W., 70½ lks. dist., marked with a partially healed blaze.
A sawed cedar stump, 22" dia., bears N.6°W., 87 lks. dist., with CS visible on open blaze.
A sawed fir stump, 18" dia., bears N.70°E., 63 lks. dist., with a healed blaze.

At corner point.

(Cont. Next Page)

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 24 & 25.

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Set an iron post, 30" long, 2" dia., 28" in the ground with
brass cap marked:

T29S R5W
 $\frac{1}{4}$ S 24
S 25
1957

Deposit local corner material alongside.

Fd. Ok by K.DeGroot, July 1997 - M124-60

Fd. OK by K.DeGroot, Aug. 1998 - M129-11