

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION SE Cor. Sec. 36 (Tsp Corner)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - James E. Freeman, under Contract #1 dated May 28, 1851 (DCSO records, Vol. 15 Page 6355)

Set a post, cor. of Tps. 29 and 30 S., between Rs. 4 and 5 W., from which

- A Redwood, 12" dia., bears N.14°W., 20 lks.
- A Redwood, 12" dia., bears S.75°W., 35 lks.
- A Redwood, 12" dia., bears N.75°E., 3 lks.
- A Redwood, 18" dia., bears S.65°E., 67 lks.

GLO resurvey by Wm. Thiel, under Contract #535 dated Feb. 5, 1889 (DCSO records, Vol. 17 Page 7008)

I restore by setting a Cedar post, 4½ ft. long, 4" sq., 24" in the ground, mkd: T29S S31 on NE., R4W S6 on SE., T30S S1 on SW., R5W S36 on NW faces, with 6 notches on each edge, from which

- A Redwood 15" bears N.14°W., 20 lks. mkd. T29S R5W S36 BT
- A Redwood 15" bears S.75°W., 35 lks. mkd. T30S R5W S1 BT.
- A Redwood 15" bears N.75°E., 3 lks. mkd. T29S R4W S31 BT.
- A Redwood 15" bears S.65°E., 67 lks. mkd. T30S R4W S6 BT.

In accordance with the field notes furnished me, all of which bearing trees I re-mark, as the old marks are overgrown & dim

G.L.O. Survey By Oscar Thiel, under Contract #658 dated May 21, 1896. (DCSO records Vol. 17 Page 7185)

The cor. of T. 29 and 30 S., Rs. 4 and 5 W., which is a cedar post 2½' above ground, 4" sq., marked and witnessed as described by the surveyor general.

John H. Markham, Jr., Engineer - Witness: George Vaughn - 1951 - C.S. File 40/179-3

All of the O.B.T.s are standing and in good shape and bear as follows:

- 12" Cedar N.75°E., 1.5'
- 15" Cedar N.17°W., 12.0'
- 16" Cedar S.76°W., 23.0'
- 24" Cedar S.66°E., 41.0'

At corner point found wood post and set 1"x30" I. P. from which:

A Fir 48" dia., bears S.80°E., 9.5', mkd T30S R4W, S6 BT. South ¼ corner Section 31 bears N.76°30'E., 700.0'.

continued next page

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION SE Cor. S 36 (Tsp Corner)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

B.L.M. Survey By Irving Zirpel, Jr. under Group #355. Surveyed July 1957/Sept. 1957. (DCSO records Vol. 28 Page 12113)

The township corner is perpetuated with an iron post, 1" dia., 10" above ground, firmly set, from which the orig. BTs as follows:

An incense cedar, 15" dia., bears N.60°E., 3 lks. dist., with W S31 visible on partially opened blaze. (Rec. bearing N.75°E.)

An incense cedar, 32" dia., bears S.65½°E., 67 lks. dist., with a healed blaze. (Rec. S.65°E.)

An incense cedar, 25" dia., bears S.76 ¾°W., 35 lks. dist., with a healed blaze. (Rec. bearing S.79°W.)

An incense cedar, 23" dia., bears N.16¼°W., 20 lks. dist., with a healed blaze. (Record)

At the corner point set an iron post, 30" long, 2" dia., 28" in the ground, with brass cap mkd:

T 29 S
R 5 W | R 4 W
S 36 | S 31
S 1 | S 6
T 30 S
1957

Cor. fd. OK, by BLM surveyors, Roseberry and Jelley, under Group #662 - Surveyed Oct. 1967/June 1969 (DCSO records, Vol. 38 Page 15512)

Fd. & used by Ronald Quimby - April 1999 - M 129-44

Fd. & used on BLM dependent resurvey by Wayne L. Rogers, Dale T. Bedell, Bryan S. Seibold, Cadastral Surveyors & Robert H. Browning, Surveying Technician, under Group #1625 surveyed Sept. 1991 thru April 1993 - (DCSO records Vol. 52 Page(s) 19772-3)

DCSO-GIS Corner visitation - 3/9/2004 - Typed: 2/8/2011 - C.S. File 67/33-1

Monument - 2½" IP/BC Comment - (Needs) rehab

FD. Ok by Ken Hoffine, 1/2006 - M149-60