

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25; 30 T29-4

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - James E. Freeman, under Contract #1 dated May 28, 1851 (DCSO records, Vol. 15 Page 6354)

Set 1/4 sec. post., from which
A Fir, 16" dia., bears S.65°W., 21 lks.
A Black Oak, 12" dia., bears S.2°30'W., 40 lks.

B.L.M. Survey By Irving Zirpel, Jr., under Group #335. Surveyed July/Sept. 1957 (DCSO records Vol. 28 Page 12108)

The 1/4 sec. cor. of secs. 25 & 30, determined at record dist. from two orig. bearing trees, as follow:

A black oak, 20" dia., bears S.1 3/4°E., 40 lks. dist., with illegible scribe marks visible on opened blaze. (Record bearing S.2°30'W.)
A fir, 21" dia., bears S.73°W., 21 lks. dist., with a healed blaze. (Record bearing S.65°W.)

At the corner point
Set an iron post, 30" long, 2" dia., 28" in the ground with brass cap mkd:
T 29 S
R 5 W * R 4 W
1/4
S 25 * S 30
1957

from which
A fir, 28" dia. bears S.84 1/2°E., 53 1/2 lks. dist. mkd. 1/4 S30 BT.
A fir 38" dia. bears S.89°W. 36 lks. dist. mkd. 1/4 S25 BT

Fd. Ok by K.DeGroot, July 1997 - M124-60

Kris DeGroot - For: Silver Butte Timber Co. - Aug. 2013 - M157-80

Fd. BC & accessories.
Geodetic coordinates:
Lat: 43°01'11.410451"N Long: 123°13'37.188961"W