

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 24; 19 T29-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - James E. Freeman, under Contract #1 dated May 28, 1851 (DCSO records, Vol. 15 Page 6353)

Set ¼ sec. post, from which
A Black Oak, 12" dia., bears N.44°E., 115 lks.
A W. Oak, 18" dia., bears S.75°W., 180 lks.

Doug. County Surveyors Office - F.C. Frear, Co. Surveyor -
Witnesses: Geo. Frank & H. Wardrip - Oct. 1918 - "Old" Cor.
Book Page 125 - Vol. 3 Page 50

Renew from Government BT. Set in a 2" Vise Screw and a Rifle
Barrel, from which
A 30" White Oak bears S.75°W., 1.80 chs.

B.L.M. Survey By Irving Zirpel, Jr., under Group #355.
Surveyed July/Sept. 1957 (DCSO records Vol. 28 Page 12110)

The ¼ sec. cor. of secs. 19 & 24, perpetuated by a rifle
barrel and vise screw, 6" below surface of the ground. This
cor. was perpetuated by F. C. Frear, D.S.C. in 1918 from the
orig. BTs., the only remaining one as follows:

A W. Oak, 30" dia., bears S.75°W., 180 lks. dist., with a
healed blaze that has been partially opened, no scribe
marks visible.

At the corner point

Set an iron post, 3' long, 2" dia., 30" in the ground, with
brass cap mkd.

T 29 S
R5W|R4W
S 24|S 19
1957

from which

A fir, 26" dia., bears N.48°E., 355 lks. dist., mkd. ¼ S19
BT

An incense cedar, 25" dia., bears S.73°W., 159 lks. dist.
mkd. ¼ S24 BT

Deposit old corner material alongside iron post.

Found B.L.M. B.C. & rifle barrel, R. Ware - 4/84 - M 96-66

Cor. Fd. OK by BLM surveyor, Boyd Peterson, under Group #1394
Surveyed Aug 1987/Jan 1988 - (DCSO records Vol. 48 Page
18525)

FD. OK, JAN 1995, M. HIEMBURGER, 1995-0045 A&B
Fd. OK by K.DeGroot, Aug. 1998 - M129-11
FD. Ok by N. Hibbs, 1/2011 - 2011-0001