

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Cor. Secs. 13, 24; 18 & 19 T 29-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - James E. Freeman, under Contract #1 dated May 28, 1851 (DCSO records, Vol. 15 Pages 6352 & 6353)

Set a post, cor. to secs. 13, 18, 19, & 24., from which
A Fir, 14" dia., bears S.55°E., 20 lks.
A Fir, 6" dia., bears N.75°E., 102 lks.
A Laurel, 12" dia., bears N.15°W., 80 lks.
A Laurel, 9" dia., bears S.76°W., 19 lks.

G.L.O. Survey by W.F. Briggs, Under special instruction dated Jan. 18, 1899 (DCSO records Vol. 15 Page 6417)

Post gone. Witness trees standing.
Made new post, 4' long, 4" sq. 24" in the ground, marked:
T29S S18 on NE., R4W S19 on SE., R5W S24 on SW., S13 on NW.,
faces, with 3 notches on N. and S. faces, from which
A Fir, 6" dia., bears N.75°E., 102 lks.
A Fir, 14" dia., bears S.55°E., 20 lks.
A Laurel, 12" dia., bears N.15°W., 80 lks.
A Laurel, 10" dia., bears S.76°W., 19 lks.

John H. Markham, Jr., Engineer - For: J.E. Pruitt -
Witnesses: C.C. Pruitt & J.E. Pruitt - July 2, 1954 - C.S.
File 41/279.

Corner set by proportional measurement.
Set - 1"x30" iron pipe and large rock, from which
A 13" Fir bears S.65°E., 21.0' mkd. S 19 BT
A 14" Fir bears N.24°E., 10.0' mkd. S 18 BT
A 6" Fir bears N.37°W., 16.0' mkd. S 13 BT
A 10" Fir bears S.22°W., 33.0' mkd. S 24 BT
West ¼ cor. S 18 (T29S R4W) bears North 2667.0'.
West ¼ cor. S 19 (T29S R4W) bears South 2600.0'.
Corner lies on a 75% North slope. Top divide lies South 650'.

B.L.M. Survey By Irving Zirpel, Jr. under Group #355.
Surveyed July/Sept. 1957 (DCSO records Vol. 28 Page 12111)

Point for the cor. of secs. 13, 18, 19 & 24, at proportionate
distance; there is no remaining evidence of the orig. cor.
Set an iron post, 30" long, 2" dia., 28" in the ground, with
brass cap mkd: T 29 S

R 5 W	R 4 W
S 13	S 18
S 24	S 19

1957

from which,
A Fir, 10" dia., bears N.58½°E., 153½ lks. dist., mkd.
T29S R4W S18 BT. (Cont. Next Page)

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Co. Secs. 13, 24; 18 & 19 T29-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir, 11" dia., bears S.11½°E., 39 lks. dist., mkd. T29S R4W S19 BT.
A Maple, 11" dia., bears S.63°W., 90 lks. dist., mkd. T29S R5W S 24 BT.
A Fir, 24" dia., bears N.3°W., 82 lks. dist., mkd. T29S R5W S13 BT.
From this point a locally established cor. bears North, 6 lks. dist., monumented with an iron post, 1" dia., 18" above ground, established and recorded by J.H. Markham, in 1954. From which locally established BTs,
A sawed fir stump, 20" dia., bears N.20½°E., 15½ lks. dist. mkd with a partially healed blaze.
A sawed fir stump, 16" dia., bears S.62°E., 32 lks. dist., mkd. with a partially healed blaze.
A fir, 13" dia., bears S.22½°W., 44 lks dist., with a partially healed blaze.
A turned-out fir, 6" dia., bears N.37°W., 24 lks. dist., with a partially healed blaze.

Found OK By G. Grubbe, Dec. 1981, R.M. 3-52

B.L.M. Survey By Boyd W. Peterson, under Group #1394. Surveyed Aug. 1987/Jan. 1988 (DCSO records Vol. 48 Page 18515)

The cor. of secs 13, 18, 19 & 24, on the W. bdy. of the Tp., monumented with an iron post, 2½" dia., firmly set, projecting 2" above ground, with brass cap properly marked. From which the remains of bearing trees mkd. by Zirpel
A fir, 15" dia., bears N.58½°E., 153½ lks. dist., with healed blaze.
A fir, 16" dia., bears S.11½°E., 39 lks. dist., with healed blaze.
A root hole bears S.63°W. 92 lks. dist. with a maple, 9" dia. lying alongside, no marks visible. (Rec. 90 lks)
A root hole bears N.3°W., 78 lks dist., with a tipped out fir stump, 14" dia., lying alongside no marks visible. (Record, 82 lks.)
and new bearing trees
A fir, 11" dia., bears S.45°W., 68 lks. dist., mkd. T29S R5W S24 BT
A fir, 15" dia., bears N.7½°W., 103 lks. dist., mkd. T 29S R5W S13 BT
(Also found Markham's 1" I.P. and 3 BTs per 1957 visit)

Fd. OK by K.DeGroot, Aug. 1998 - M129-11

continued next page

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Co. Secs. 13, 24; 18 & 19 T29-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Dan Saily- For: Lone Rock Timberland Co. - 9/2021 - M180-11

Found - 1957 BLM brass cap mkd T29S R5W S13 S24 R4W S18 S19
24" D.Fir bears S.45½°W., 44.0 ft (record S.45°W.,
44.88 ft) well healed face and BLM tag
25" D.Fir bears S.12°E., 26.7 ft (record S.11½°E.,
25.74 ft) well healed face and county tag
26" D.Fir bears found at record N.58½°E., 101.31 ft
well healed face and BLM tag (did not measure).
Markham 1.5 ft tall iron pipe found at record, with
aluminum post beside
23" D.Fir bears S.27½°W., 24.0 ft (record BT for
Markham pipe) well healed face and BLM tag
Did not search for record root holes N.3°W., 51.48
ft and S63°W 60.72 ft.
Note - Corner lies on steep North slope, approximately 100
ft East of side ridge running NW. Top of corner
monument is 0.2 feet above ground level aluminum
U-post 0.4 feet South.
BT distances are to an aluminum nail in the side
center and bearings were derived from angular
measurements to an aluminum nail in the face of
the tree.

Fd as per rec. 11/2022 - B. Knapp - M181-51