

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13; 18 T29-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - James E. Freeman, under Contract #1 dated May 28, 1851 (DCSO records, Vol. 15 Page 6352)

Set 1/4 sec. post, from which
A W. Oak, 7" dia., bears N.78°W., 38 lks.
A B. Oak, 18" dia., bears S.50°E., 40 lks.

GL0 Survey by W. F. Briggs, Deputy Surveyor, under Special Instructions dated Jan. 18, 1899 (DCSO Records, Vol. 15 Pages 6416-17)

1/4 S. Cor. post gone, trees standing.
Made new post, 3 ft. long, 3" sq., 24" in the ground mkd. 1/4 S 18 on E.; S13 on N. face, from which
W.Oak 8" dia., bears N.78°W., 38 lks.
B.Oak 12" dia., bears S.50°E., 40 lks.

Doug. County Surveyors Office - Ben B. Irving - Witnesses: J. Byron & R. Irving - July 24, 1953 - C.S. File 45/234

Set - A 1"x30" Iron Pipe with brass cap 18" above ground, mound of stone. Postive identification by both original bearing trees.
BTs - 24" W.O. S.80°E., 37' mkd: 1/4 S18 CS BT
O.B.T. N.18°W., 38 lks (24" W.O.) and mkd: 1/4 S13 CS BT.
Orig. record showed this BT N.78°W., should be N.18°W.

B.L.M. Survey by Irving Zirpel, Jr., under Group #355. Surveyed July 1957/Sept. 1957 (DCSO records Vol. 28 Page 12112)

The 1/4 sec. cor. of secs. 13 and 18, perpetuated at record dist. from 2 orig. bearing trees by an iron post, 1" dia., 18" above ground, firmly set, and in a mound of stone, 2' base, 1' high, with brass cap mkd: County Surveyor

1/4
R S | S R
5 13 | 18 6
W T 29 S W
Office

from which original BTs
A Black Oak, 40" dia., bears S.47°E., 40 lks. dist., with scribe marks 1/4 visible on opened blaze. (Record bears S.50 E.) (Cont. Next Page)

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13; 18 T29-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A White Oak, 26" dia., bears N.24½°W., 38 lks dist., with an opened and rotten blaze no scribe marks visible; remarked S13 CS BT by county surveyor. (Record bearing N.78°W.)

Newly established BT by county surveyor

A white oak, 22" dia., bears S.82¼°E., 56 lks. dist., marked ¼ S18 CS BT on a double blaze.

At corner point

Set an iron post, 30" long, 2" dia., 28" in the ground, and in a mound of stone, 2' base, 1' high, with brass cap mkd;

T 29 S
R 5 W | R 4 W
¼
S 13 | S 18
1957

Deposit county surveyor cor. alongside iron post.

Fd. BC - Dave Beedle, 12/2009 - M160-33

Brent Knapp - For: Lone Rock Timber Co. - 11/2022 - M181-51

Found - BLM brass cap alongside DCS0 brass cap.
W.Oak, N.24°W., 25.1', healed scar.
W.Oak, S.82°E., 36.96', healed scar (Faint)
Set - Metal post, 5' north
Metal post, 5'west.