

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 040010

PRIMARY CORNER DESCRIPTION N NE Cor. Clark DLC #40

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

Original - Bowman and Burnett, under Contract dated Sept. 1855

-----  
Set post marked from which  
A W.Oak 30" dia., bears S.80°W., 342 lks.

Arthur Boyer - Wit: A. Wecks and T. Shattenkirk - Feb. 1953 - C.S. File 41/115

-----  
Set 3/4" Bolt from found O.B.T., a 30" W.Oak, S.80°W., 226 ft.

DCSO-GIS Corner visitation - 8/24/2004 - Typed: 2/1/2011 - C.S. File 67/33-1

-----  
Monument - 3/4"  
Comment - (needs) rehab

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch - Feb. 28, 2011 - C.S. File 67/33-15

-----  
Found - A 3/4" bolt w/1" sq. top protruding 2" above ground. (1953 Boyer)  
Orig. 30" dia., W.Oak BT. Now fallen intact with no bark and rotted face bears S.80°W., 225.7 ft. (as per rec.)

New - Found monument is very stable we do not set BC.  
Brg & dist. taken from 3/4" bolt.  
6" DBH D.Fir scribed "X" on high blaze & "CS BT" on low blaze bears N.11½°E., 59.2 ft.  
8" DBH Madrone scribed "NNE DLC 40 CS" "BT" on a double blaze, bears N.69°E., 8.3 ft.  
13" DBH W.Oak scribed "NNE DLC 40 CS" "BT" on a double blaze, bears S.17¼°W., 46.7 ft.  
19" DBH W.Oak scribed "NNE DLC 40 CS" "BT" on a double blaze, bears N.54½°W., 36.4 ft.

Note - Monument is on a moderate west slope w/mix oak, madrone & D.Fir trees.  
A Roseburg Forest Products Rock Quarry is north of monument.  
Decl. 15¾°E