

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 042040

PRIMARY CORNER DESCRIPTION S SE Cor. Burnett DLC #42

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Original - Bowman and Burnett, under Contract dated Sept. 1855 (DLC survey)</p> <p>-----</p> <p>Set a post, marked, from which A W.Oak 16" dia., bears N.41°W., 150 lks.</p>
<p>F.C. Frear, Deputy Co. Surveyor - For: O.W. Ronk, Fred Smith and L.N. Sargisson - May 1919 - Vol. 3 Pgs. 62-64; F.B. 46 Pgs. 47-57 (and "old" corner book, pg. 130)</p> <p>-----</p> <p>I reset from 30" W.Oak N.41°W., 150 lks. Remarked. Set a 3/4" x 36" Iron rod for corner, from which A 4" W.Oak bears S.37°E., 52 lks. C.S.B.T.</p>
<p>Douglas Co. Surveyors Office - Bruce R. Rogers, Deputy - Mike Stone, crew - June 15, 1965 - C.S. File 49/139-119</p> <p>-----</p> <p>Found - Orig. 16" Oak, now 30", N.41°W., 99.0 ft., shows good scar. Did not open. 3/4" iron rod at corner. No trace of Frear's tree. New BT - 4" W.Oak S.25°W., 34.4 ft. marked.</p>
<p>DCS0-GIS Corner visitation - 8/19/2004 - Typed: 2/1/2011 - C.S. File 67/33-1</p> <p>-----</p> <p>Monument - BC/IP - 3/4" Comment - (needs) rehab</p>
<p>Raymond Brown - For: Cow Creek Band of the Umpqua Tribe of Indians - Sept. 2006/June 2007 - RM 4-14</p> <p>-----</p> <p>Fd. brass cap. per PLSS ID #042040</p>
<p>Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch - Garrett McGraw - Feb. 24, 2011 - C.S. File 67/33-10</p> <p>-----</p> <p>Found - A 3/4" iron rod firmly set and protruding 2" above ground. 1919 Frear A W.Oak 16" dia., now a 2 1/2 ft. tall 36" dia., W.Oak stump which is now bark-less and has a rotted center with no face or scribing remaining; bears N.41°W., 99.0 ft. (as per rec) Orig. Frear renewal tree gone. A 4" W.Oak now a 16" DBH W.Oak with no evident blazing; bears S.27 1/2°W., 34.4 ft. (rec. S.25°W., 34.4 ft.) 1965</p> <p>continued next page</p>

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 042040

PRIMARY CORNER DESCRIPTION S SE Cor. Burnett DLC #42

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New - A 1/2" dia., steel rebar stamped "B0" on its top which is set vertically in the south westerly corner of a 7½x4x2 ft. tall concrete water trough; bears N.14¼°E., 176.6 ft.  
A 29" DBH W.Oak scribed "SSE DLC 42 CS" "BT" on a double blaze; bears S.65½°E., 111.0 ft.

Note - Monument is in open pasture on gentle northwesterly slope.  
Dec. 15¾°E.