

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 043040

PRIMARY CORNER DESCRIPTION W NW Cor. Dooley DLC #43

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Original - Bowman and Burnett, under Contract dated Sept. 1855 (DLC survey)</p> <p>-----</p> <p>Set a post from which</p> <ul style="list-style-type: none">A B.Oak 3" dia., bears S.5°E., 26 lks.A B.Oak 6" dia., bears N.35°W., 32 lks.
<p>Frank Cain - April 28-29, 1916 - F.B. 64 Pg. 35 (and "old" corner book, pg. 128)</p> <p>-----</p> <p>No evidence of original BT at proper distance. Set Fir post 4" x 4" x 3½ ft. marked C.S. C43 T29S R6W, from which</p> <ul style="list-style-type: none">A Fir 36" dia., marked C.S. C43 T29S R6W, bears N.67°40'E., 86 lks.A Fir 32" dia., marked C.S. C43 T29S R6W, bears N.51°30'W., 26 lks.
<p>Corner looked for, <u>not found</u>, Nov. 10, 1970, C.S. File 49/139-135 Douglas County Surveyors Office</p>
<p>Carl Sweeden - For: Harrison Rice - 1/2016 - M170-48 A&B</p> <p>-----</p> <p>Set - 5/8" I.rod w/RPC "SWEEDEN LS 2752" up 0.70' from 1916 BTs:</p> <ul style="list-style-type: none">Fd - 36" D.Fir BT, N.67°40'E., 56.76' now very rotten stump with scribing visible and axe marks32" D.Fir BT, N.51½°W., 17.16' now very rotten stump with scribing visible and axe marksNew - 12" D.Fir BT, S.55°E., 12.25', scribed "C43 T29S R6W BT", mag nail w/brass washer "LS 2752" set in bole & tag18" D.Fir BT S.52°W., 14.0', scribed "C43 T29S R6W BT", mag nail w/brass washer "LS 2752" set in bole & tag.
<p> </p>