

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 043060

PRIMARY CORNER DESCRIPTION SE Cor. Dooley DLC #43

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Original - Bowman and Burnett, under Contract dated Sept. 1855 (DLC survey)</p> <p>-----</p> <p>Set a post from which A Fir 5" dia., bears N.70°E., 17 lks. A W.Oak 6" dia., bears S.65°W., 27 lks.</p>
<p>Frank Cain - April 28-29, 1916 - F.B. 64 Pg. 35 (and "old" corner book, pg. 128)</p> <p>-----</p> <p>Renew by original BT, decayed and fallen down but marks plain. Set an Oak post marked C.S. C43 T29S R6W, from which A Fir 14" marked C.S. C43 T29S R6W bears N.56¼°E., 15 lks. A Fir 17" marked C.S. C43 T29S R6W bears N.35 3/4°W., 50 lks.</p> <p>Above corner established in presence of E.L. Rice, S.S. Swickard and S.C. Meriaith</p>
<p>Douglas Co. Surveyors Office - John Powell, Deputy - W.Penley J. Heritage, crew - Nov. 10, 1970 - C.S. File 49/139-134</p> <p>-----</p> <p>Found - 14" D.Fir, now stump N.36°W., 33.0 ft. opened and burnt faint scribe marks visible. 17" D.Fir now stob, N.56°E., 9.9 ft. opened for scribing, "S 29" and other marks.</p> <p>Set Brass cap at cor. mkd: County Surveyors T 29 S R 6 W Office 1970 SE <u>DLC 43</u></p> <p>New BTs -12" Maple N.65°E., 69.0 ft. scribed "SE DLC 43 CSBT 10" W.Oak S.18°W., 72.5 ft. scribed "SE DLC 43 CSBT This corner is approx. 10 ft. South of draw.</p>
<p>Fd. OK, by Howard Johnstone, Dec. 1989, M 101-72 Fd. Brass cap &amp; 3 BTs, 1/2016 by C Sweeden M170-48 A&amp;B.</p>
<p> </p>