

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 045030

PRIMARY CORNER DESCRIPTION SW Cor. A.D. Willis DLC #45

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Bowman and Burnett, under Contract dated Sept. 1855 (DLC survey)

-----  
Set a post from which  
A Fir 4" dia., bears South 16 lks.

Frank Cain - Feb. 19, 1915 - Vol. 2 Pg. 201 and Pg. 267 (and "old" corner book, pg. 129)

-----  
Post 4" x 4" x 3½ ft. marked C.45 T29S R6W, from which  
A Fir 48" dia., marked C.45 X bears S.70°W., 11 lks.  
Corner established in presence of O.L. Willis, Frank Royer and Clive Willis.  
Corners renewed by original BTs where found and in other case at proper distances.

Survey by Victor McLind - April 1, 1971 - C.S. File 55/196 and M 42-22

-----  
Found - 48" Fir on ground with blaze and "X" as per Cain in 1915.  
Established corner N.70°E., 11 lks. (7.3 ft.) from hole in ground where Fir stood.  
Set 5/8" Iron rod at corner.  
New BTs -13" D.Fir N.76°E., 15.2 ft.  
9" D.Fir S.23°W., 25.6 ft.  
Both BTs scribed "C45 BT".  
The West line of DLC 45, as controlled by this corner, fits closely an old fence running North from S. line of Sec. 21. Position of corner falls within 3 ft. of position calculated using proportioned distances and rotated bearings.