

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 045040

PRIMARY CORNER DESCRIPTION S SE Cor. A.D. Willis DLC #45

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Bowman and Burnett, under Contract dated Sept. 1855 (DLC survey)

Set a post from which
An Alder 6" dia., bears N.15°E., 20 lks.
A Maple 7" dia., bears S.30°E., 15 lks.

Frank Cain - Feb. 19, 1915 - Vol. 2 Pg. 267

Fir post 4 x 4 x 3½ marked C.45 T29S R6W, from which
A Maple 14" dia., marked C.S. C45 T29S R6W bears S.20°W.,
8 lks.
A Maple 16" dia., marked C.S. C45 T29S R6W bears N.72°W.,
72 lks.

J.W. Cole - Survey for Rice Bros. - 1924 - Field Book 90 Page 46

Set Iron pipe 3/4" x 40" at SE cor. DLC 45 - T29-6

Douglas Co. Surveyors Office - John Powell, Deputy, and crew
- April 19, 1971 - C.S. File 49/139-139

Found - 14" Maple now 20", S.20°W., 5.3 ft. scribe visible
"45 29S R6W". Rotten face.
16" Maple now 22" N.72°W., 47.5 ft. Shows scar.
Set Brass cap at cor. mkd: County Surveyors T 29 S R 6 W
Office 1971 S.E.
DLC 45

New BT - 10" Cedar S.7°W., 58.6 ft. scribed "S.E.DLC 45 CS
BT"
This cor. falls approx. 70.0 ft. West of Willis Creek.

Douglas Co. Surveyors Office - Randall Smith & Stephen Flause
- Feb. 5, 1996 - C.S. 64/66-3

Mon. Fd. - 2½" Brass cap on a 1½" O.D. Iron pipe protrudes
14" above ground.
Accessories Fd. -
14" now 24" dia. Maple, with an unhealed rotted
blaze, no marks visible, bears S.20°W., 5.3'.
16" now 32" dia. Maple, with a fully healed
blaze, bears N.72°W., 47.5'.

(Cont. Next Page)

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 045040

PRIMARY CORNER DESCRIPTION S SE Cor. A.D. Willis DLC #45

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

10" now 13" dia. 1' high rotting cedar stump, with scribing visible "BT", bears S.7°W., 58.6'.
Mon. Set - The "W" of S.W. is obliterated and an "SE" is stamped. This was done to correct errant corner marks of 1971 renewal.
New Accessories -
Double trunked Myrtle, double blazed and scribed "SSE DLC 45 CS BT" on 10" dia. S'ly trunk, root crown bears N.22°W., 43.9'.
10" dia. W.Oak, double blazed and scribed "SSE DLC 45 CS BT", bears S.23°W., 51.6'.

Fd. BC 10/2014 - R. Quimby - M166-20