

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 046010

PRIMARY CORNER DESCRIPTION NE Cor. Gilliland DLC #46

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Bowman and Burnett, under Contract dated Sept. 1855 (DLC survey)

Set a post from which
A W.Oak 14" dia., bears West 25 lks.
A B.Oak 8" dia., bears S.35°E., 20 lks.

G.G. Stewart, D.C.S. - Wit: Abner Rue; J.H. Adams; Dick Redding and H. Erskine - April 17-19, 1922 - Vol. 3 Pg. 118 (and "old" corner book, pg. 131)

No witness trees could be found and witnesses said they had washed out. I ran a true line due North from Exterior L corner, 2157.7 ft. and set a witness corner. Drove galv. Iron bar for witness corner 86.3 ft. South of true corner which falls in river. Marked:
A 6" W.Oak N.88°W., 13.0 ft.
A 6" W.Oak S.83°E., 36.6 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - John Fee Ray Irving, crew - June 1954 - C.S. File 46/45-1(I)

Found - ½" bolt at witness corner.
Old BTs established by Stewart, 1922, standing and in good condition.
The 6" W.O. N.88°W., 13.0 ft. has been cut out and scribing visible.
Both Oak trees check for bearing and distance.
Rescribed:
14" W.O. S.83°E., 36.6 ft. "WC NE C 46 CS BT"
Blazed and scribed:
6" forked Ash W.C. N.E. C46 CS BT, bears S.61°W., 13.6 ft.
6" W.O. W.C. N.E. C46 CS BT, bears S.37°W., 11.8 ft.
24" W.O. WC NE C46 CS BT, bears S.17°E., 75.8 ft.
N-S fence ends at corner. Corner on bank of river.