

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 046040

PRIMARY CORNER DESCRIPTION SE Cor. Gilliland DLC #46

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Bowman and Burnett, under Contract dated Sept. 1855 (DLC survey)

Set a post, from which
 A B.Oak 21" dia., bears West, 26 lks.
 A B.Oak 4" dia., bears N.75°W., 77 lks.

Frank Cain - For: Rice Bros. - June 3, 1915 - F.B. 37 Page 46

Set SE Cor. to C. 46.
Mark - A Fir 14" dia., S.85°W., 41 lks.
 A Fir 18" dia., N.40°W., 45 lks.

G.G. Stewart - D.C.S. - Wit: Abner Rue, J.H. Adams, Dick Redding, H. Erskine - April 17-19, 1922 - Vol. 3 Pg. 118 (and "old" corner book, pg. 131)

Found stake set by previous surveyor who was reputed to have run it in from SW corner. Could not find BTs.
Set squared Oak post and marked:
 A 12" Fir N.84°E., 27.5 ft.
 An 18" Fir N.41½°W., 30.0 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - John Fee Ray Irving, crew - June 7-14, 1954 - C.S. File 46/45-1(H)

Found - BTs as established by Stewart in 1922, standing and healthy.
Set 1" x 40" Bolt (square head) at corner.
Blazed and scribed:
 6" W.Oak N.81°E., 6.6 ft. C46 CS BT.
We cut out:
 Old BT 24" Fir S.84°W., 27.5 ft. (Rec. bearing N.84°E.) scribing in good condition.
We did not cut out:
 Old blaze 30" Fir N.41½°W., 30.0 ft. Looks good and check for bearing and distance.