

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 046050

PRIMARY CORNER DESCRIPTION Int. SE Cor. Gilliland DLC #46

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

<p>Original - Bowman and Burnett, under Contract dated Sept. 1855</p> <p>-----</p> <p>Set a post from which An Ash 5" dia., bears S.65°W., 75 lks. A B.Oak 6" dia., bears N.75°E., 86 lks.</p>
<p>G.G. Stewart - For: Rice Bros. - Wit: Abner Rue; J.H. Adams; Dick Redding and H. Erskine - April 17-19, 1922 - Vol. 3 Pg. 118 (and "old" corner book, page 131)</p> <p>-----</p> <p>Set Iron bolt 8 ft. long for corner. Found O.B.T. Marked: A 16" B.Oak S.9°E., 62.0 ft. A 16" W.Oak N.71½°E., 57.8 ft. O.B.T.</p>
<p>Douglas Co. Surveyors Office - James Byron, Deputy - John Fee Ray Irving, crew - June 1954 - C.S. File 46/45-1(L)</p> <p>-----</p> <p>Found - Bolt and 2 ft. post scribed CS C46. Both BTs as established by Stewart, 1922. 16" B.O. S.9°E., 62.0 ft. stump only, center rotted. 24" W.O. N.76°E., 57.8 ft. (Rec. N.71¼°E.) Blaze grown over, we did not cut out.</p> <p>Blazed and scribed: 14" R.Fir S.56°E., 66 ft. "Int. L-C46 CS BT." Power pole C 5706 - 1954 - N.60°E., 18.2 ft. dist.</p>
<p> </p>