

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 046060

PRIMARY CORNER DESCRIPTION E SE Cor. Gilliland DLC #46

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Bowman and Burnett, under Contract dated Sept. 1855 (DLC survey)

Set a post from which
A Laurel 3" dia., bears S.3°E., 9 lks.

G.G. Stewart - Wit: Abner Rue; J.H. Adams; Dick Redding; and H. Erskine - April 17-19, 1922 - Vol. 3 Pg. 118 (and "old" corner book, pg. 131)

Set Iron bolt 3 ft. long for corner at stake set by running East from Interior L corner. There was a marked stake set at this position by former surveyor, but if set from O.B.T. or not, I could not tell. Several trees chopped into but any scribe marks they may have had were gone. I marked:
A 24" Fir N.31°E., 15.3 ft.
A 24" Fir N.84°W., 59.0 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - John Fee Ray Irving, crew - June 1954 - C.S. File 46/45-1(L)

Found - 3/4" iron bolt at 3 way fence corner.
36" Fir stump N.31°E., 15.3 ft. (which we cut out) scribed 46.
36" Fir alive and standing, N.84°W., 59.0 ft., blaze grown over. We did not cut it out.
Blazed and scribed:
12" R.Fir S.51°W., 20.2 ft. "SE Ext. L CL 46 CS BT.
10" R.Fir S.60°E., 26.2 ft. "SE Ext L CL 46 CS BT.