

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 100140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec 31; & 36 of T29-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6456)

Set 1/4 sec. post, from which:
A Laurel, 6" diam., bears N.65°E., 6 lks.
A Laurel, 10" diam., bears N.5°W., 5 lks.

W. F. Briggs, Co. Surveyor - for David Thompson - Nov. 1887
-Vol. 1 Pg. 108

Set ¼ post from which
Pine, 20" diam., bears N.27°E., 2.54 chs.
Pine, 20" diam., bears S.22°W., 3.53 chs.

Re-establishment of corners - Fred Mensch U.S. Deputy Surveyor - under date of Dec.4, 1905 (DCSO records, Vol. 15 Page 6506)

Set a sandstone 12x8x6", 8" in the ground mkd. 1/4 on W. face, from which:
A Red Fir, 8" diam., bears S.88°E., 27 lks., mkd. ¼ S31 BT
A Red Fir, 20" dia., bears S.68°W., 18 lks., mkd. ¼ S36 BT

Fd. Post, GLO survey by Roy Campbell, Contract #789 dated Aug. 21, 1909 (DCSO Records. Vol. 15 Pg.6515)

James W. Byron, Deputy - Wit. S.A. Bilow - Apr. 27, 1959 - C.S. 49/139-2

Found - 1" iron pipe at corner & both orig. BT's.
Found stone at corner chiseled ¼.
Orig. SW BT., now stump, shows good scar.
Orig. SE BT., now dead, shows good scribing "BT"
New BTs -20" R. Fir, bears S.11°E., 5 ft. scribed S31 ¼ CS BT
8" W. Fir, bears N.53°W., 44.1 ft. scribed ¼ S36 CS BT.

BLM - Resurvey Lynn Roseberry, Cadastral Surveyor - Group #669 Apr 1968 (DCSO records, Vol. 35 Page 14453)

Cor. monumented with the original sandstone, 12x8x5", firmly set, 10" in the ground, mkd. 1/4 on W. face, with an iron pipe driven alongside, 1" diam., protruding 8" above ground, firmly set, from which the original bearing trees:
A fir snag, 12" diam., bears S.88°E., 27 lks., with scribe marks BT visible on partially opened blaze.
(Cont. on Next Page)

