

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. Cor. 19 & 30 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6455)

Set a post corner of secs. 19, 24, 25, 30, from which:
A maple 6" diam., bears S.25°E., 42 lks.
A maple 8" diam., bears S.15°W., 23 lks.
A myrtle 8" diam., bears N.45°W., 31 lks.
A cedar 18" diam., bears N. 35°E., 15 lks.

Re-establishment of corners by Fred Mensch, US Dep. Surveyor, under contract #757 - July 28, 1905 (DCSO Vol 15 Pg 6504-05)

This corner has evidently been restored at a later date than that of the original survey. I find, however, one of the original bearing trees still standing and re-establish the cor in its original position as follows: destroying former cor and marks on bearing trees :
Set a sandstone 16x10x4", 11" in the ground for cor. of secs., 19, 24, 25 and 30, mkd. with 4 notches on N. and 2 notches on S. edge, from which:
A maple, 18" diam., bears N.53°E., 11 lks., mkd. T29S R6W S19 BT.
A maple, 14" diam., bears S.75°E., 18 lks., mkd. T29S R6W S30 BT.
A maple, 12" diam., bears S.3°W., 14 lks., mkd. T29S R7W S25 BT.
A maple 20" diam., bears N.35°W., 23 lks., mkd. T29S R7W S24 BT.

Ben B. Irving, Dep. Co. Surveyor - May 1934 - M 1-27

NW Sec. 30
Yew wood anchor post for fence

James W. Byron, Dep. Co. Surveyor - Dale McFarland and John Powell - Apr 1962 - C.S. 49/139-36

Standard Corner for Sections 19 and 30, T29-6
Found - Yewwood Anchor post,
We do not find Original BT's
Set - Brass cap along W. edge of Anchor post & mkd:
County Surveyor's Office 1962
T 29 S
R7W | S19 R 6
 | S30
New BTs -10" R. Fir bears S.88½°E. 101.5 ft., scribed S30 T29S R6W CS BT
5" Maple, bears N.15°E., 41.3 ft, scribed S19 CS BT.
continued next page

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. Cor. 19 & 30 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Fd. OK, Aug. 1989, H. Johnstone, M 101-60.
Fd. OK, Dec. 1989, H. Johnstone, M 101-73.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2270, Surveyed May/Aug. 2009 - (DCSO records Vol. 57 Page(s) 22721-2)

The cor. of secs. 19 and 30 only, perpetuated by person(s) unknown, recovered by Irving, in 1934, perpetuated by Byron, in 1962, and is accepted as the best available evidence of the original cor. position, monumented with a yew fence post, 5 ft. high, 6" dia., (an iron post, 1 1/4" dia., firmly set, projecting 14" above ground, with a BC mkd. COUNTY SURVEYORS OFFICE T29S R6W R7W S19 S30 1962 bears West, 0.6 ft.)

from which a bearing tree mkd. by Byron

A myrtle, 11" dia., bears N.14 1/4°E., 43.3 ft., with a healed double blaze.

and a new bearing tree

A maple, 9" dia bears S.31 1/4°E., 75.0 ft., mkd. T29S R6W S30 BT.

Corner is the fence post at intersection of barbed and woven wire fence lines extending S.3°W. and E.