

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 100302

PRIMARY CORNER DESCRIPTION E. Sec Cor. 24 & 25 only, T29-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Retracement - BLM - Roy T. Campbell, Dep. Surveyor - under contract # 789, July 4, 1910 (DCSO Vol. 16 Pg. 6564)

Intersect E. bdy. of Tp., 1.58 chs. N. of the corner which is a post, 4" sq. 12" above ground, firmly set, marked and witnessed as described by the Surveyor General.

At the point of intersection with the E. bdy. of Tp. I set a conglomerate stone, 15x12x8"., 10" in the ground, for C.C. for secs. 24 and 25, marked C.C. on the W., with 2 grooves on S. and 4 grooves on N. face, from which:

A Ash, 18" diam., bears S.55°45'W., 293 lks., Mkd. T29S
R7W S25 BT

A Fir, 24" diam., bears N.82°W., 161 lks., Mkd. T29 R7W
S24 BT

Ben B. Irving - Deputy Co. Surveyor - Wit. N. E. Richardson, Frank Royer, Robinette, Bill Weightman - May 1934- M 1-27 & C.S. 37/171

Rock as described in Government field notes. One original B.T. stump remains. No new trees suitable for marking close

James W. Byron, Deputy County Surveyor - Dale McFarland and John Powell - Apr 1962 - C.S.49/139-35

Found - Corner Stone with "C" chiseled on face. We find corner stone at base of fence corner post and out of ground. Do not find NW BT. This area in yard. We check record bearing S.2°W (See B.B.I. Survey) & record dist. to standard corner

| S19 T29S
| S30 R6W

Set - Brass Cap at fence corner & Mkd: CC S24 | T29S
County Surveyor's Office, 1962 R7W S25 | R6W

New BT: 9" maple, bears S.64°W., 22.6 ft. scribed CC S25 BT.
Fences run North, Southerly and West from corner.

Fd. Ok, Aug. 1989, H. Johnstone, M 101-60
Fd. Ok, Dec. 1989, H. Johnstone, M 101-73 (See map for Cedar BT not previously noted)

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2270, Surveyed May/Aug. 2009 - (DCSO records Vol. 57 Page(s) 2272)

The closing cor. of secs. 24 & 25 only, on the W. bdy. of the Tp., perpetuated by Byron, in 1962, from original evidence no longer in existence, subsequently perpetuated by ... cont.

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 100302

PRIMARY CORNER DESCRIPTION E. Sec Cor. 24 & 25 only, T29-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

... Johnstone, (PLS) No. 498, in 1989, monumented with an iron post, 36" long, 1¼" dia., firmly set, bent S., projecting 20" above ground, with brass cap (properly) mkd. from which a bearing tree mkd. by Byron
A maple, 18" dia. bears S.61¼°W., 22.6 ft., with a healed blaze.
and a bearing tree mkd. by Johnstone
A cedar, 22" dia., bears N.55¼°W., 202.3 ft., with a healed blaze.
Reset iron post, 36" long, 33" in the ground.
Corner is located S., 170 ft. from Rice Creek Road, asphalt surfaced 23 ft. wide, bears N.65°E. and S.65°W., at the intersection of a barbed and woven wire fence extending N. with a broken down barbed wire fence extending W.

Fd. as per 2011 BLM resurvey; Set 6 ft. steel post 0.5 ft West. - by D Edwards, 6/2016 - M172-16