

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 100341

PRIMARY CORNER DESCRIPTION East 1/4 cor sec. 24 (only) T29-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Original - Nathaniel Ford, Under Contract #44 dated May 30, 1854 (DCSO Vol.15 Page 6455)</p> <p>-----</p> <p>Set 1/4 sec. post, from which: A B Oak, 10" diam., bears S.35°E., 52 lks. A Laurel, 18" diam., bears N.49°W., 25 lks.</p>
<p>Howard Johnstone - for Roseburg Resources - Aug. 30, 1989 - M 101-60</p> <p>-----</p> <p>Set - 5/8" x 48" iron rod and alum. cap mkd. "1/4 Cor Sec 24 only". New BTs - 10" fir, S.36°W., 3.2 ft. "1/4 S24 BT." 21" fir, N.51°W., 5.7 ft. "1/4 S24 BT."</p>
<p>BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2270, Surveyed May/Aug. 2009 - (DCSO records Vol. 57 Page(s) 22723)</p> <p>-----</p> <p>The ¼ sec. cor. of sec. 24 only, on the W. bdy. of the Tp, reestablished by proportionate measurement by Johnstone, in 1989; there is no remaining evidence of the original cor., therefore this position is accepted as the cor., monumented with an iron rod, 5/8" dia., firmly set, projecting 17" above ground, with an aluminum cap (properly) mkd. from which bearing trees mkd. Johnstone A fir, 12" dia bears S.32½°W., 3.3 ft., with a healed blaze. A fir, 26" dia., bears N.52¼°W., 57 ft., with a healed blaze.</p>
<p> </p>