

PRIMARY CORNER DESCRIPTION 1/4 cor. for sec 18; & sec. 13 of T29-7

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6454)

-----  
Set 1/4 sec. post, from which:  
A Laurel, 24" diam., bears S.50°E., 16 lks.  
A B. Oak, 15" diam., bears S.30°W., 50 lks.

Clifford M. Bryden, Surveyor of Roseburg Lumber Co. - May 21 1957 - M 5 - 41

-----  
Location of corner established by proportional measurement  
Set 3/4" iron pipe from which:  
A fir, 14" diam., bears S.78°50'E., 36.6 ft., scribed ¼  
T29S, S 18 BT.  
A fir, 12" diam., bears S.62°W., 70.7 ft., scribed ¼ T29S,  
S 13 BT.

BLM Resurvey - Hans W. Thielsen, Group #346. Apr/May 1957 (DCSO records, Vol. 28 Page 12145)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 3 ft. long, 1" diam., 28" in the ground with brass cap marked  
T29S  
R7W|R6W  
¼  
S13|S18  
1957

from which:  
A fir, 17" diam., bears S.6°E., 72 lks., mkd. ¼ S18 BT.  
A fir, 12" diam., bears N.35¼°W., 90 lks., mkd. ¼ S13 BT.

BLM Resurvey - Hans W. Thielsen, Group #346. Aug 1959 (DCSO records, Vol. 30 Page 12803)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 3 ft. long 1" diam., 28" in the ground, with brass cap marked:  
T29S  
R7W|R6W  
¼  
S13|S18  
1957

from which:  
A fir 17" diam., bears S.89°E., 95 lks., mkd. ¼ S 18 BT.  
A fir 12" diam., bears N.19°W., 81 lks., mkd. ¼ S 13 BT

continued next page

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 100440

PRIMARY CORNER DESCRIPTION 1/4 cor. for sec 18; & sec. 13 of T29-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2270, Surveyed May/Aug. 2009 - (DCSO records Vol. 57 Page(s) 22725-6)

-----  
The ¼ sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp., determined at record bearing and dist. from the remains of the bearing trees mkd. by Thielsen

A sawed fir stump, 6 ft. high 21" dia., bears S.89°E., 62.7 ft. with a healed blaze.

A sawed fir stump, 29" dia. bears N.19°W., 53.5 ft., with scribe marks ¼ S13 BT visible on a partially opened blaze

Thielsen's iron post, 36" Long, 1" dia. was found lying loose on the ground nearby in an unrelated position

At the corner point

Reset the iron post, 36" long, 1" dia. 28" in the ground and add marks 2009 to the brass cap to now read

¼  
S13|S18  
R7W|R6W  
T29S  
2009  
1957

from which new bearing trees

A fir 6" dia. bears S.58¼°E., 23.6 ft., mkd. ¼ S18 BT.

A fir 12" dia. bears N.9½°W., 13.4 ft. mkd ¼ S13 BT.

Corner is located in a barbed and woven wire fence extending N and S.