

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7,18; 12 & 13 T29-7

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6454)

Set a post corner from which:

- A Maple, 8" diam., bears N.80°W., 40 lks.
- A Maple, 7" diam., bears N.75°E., 36 lks.
- A Laurel, 10" diam., bears S.15°W., 35 lks.
- A Laurel, 10" diam., bears S.35°E., 50 lks.

Clifford M. Bryden - Survey for Roseburg Lumber Co. - May 21, 1957 - M 5 - 41.

Location of corner established by portional measurement.
 Set 1" iron pipe for corner from which:

- A Maple, 14" diam., bears N.77°30'E., 70.2 ft. scribed T29S R6W S7 BT.
- A Maple, 16" diam., bears S.41°10'E., 86.8 ft. scribed T29S R7W S18 BT.
- A Fir, 14" diam., bears S.70°W., 125.0 ft. scribed T29S R7W S13 BT.

No trees in Northwest quater.

BLM Resurvey by Hans W. Thielsen - under group # 346 - surveyed Apr/May 1957 (DCSO Vol. 28 Pg. 12146)

Point for the sec. cor, there is no remaining evidence of the original corner.
 Set an iron post, 3 ft. long, 2" diam., 28 " in the ground with brass cap mkd.:

T29S	
R7W	R6W
<u>S12</u>	<u>S 7</u>
S13	S18
1957	

from which

- A maple, 12" diam., bears S. 21 3/4°E., 121 lks., mkd. T29S R6W S18 BT.
- A fir, 16" diam., bears S.77°W., 189 lks., mkd. T29S R7W S13 BT.

There are no bearing objects or bearing trees convenient in secs. 12 or 7.

BLM Resurvey - Hans W. Thielsen - Under group # 346 - Surveyed Aug 1959 (DCSO Vol. 30 Pg. 12803-04)

Point for the cor. of secs. 7, 12, 13 and 18, at proportionate distance, there is no remaining evidence of the original corner. (Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18; 12 & 13 T29-7

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

Set an iron post, 3 ft., 2" diam., 28" in the ground, with brass cap mkd.:

T29S
 R7W | R6W
 S12 | S 7
 S13 | S18
 1957

from which:

A maple, 10" diam., bears N.80°E., 109 lks., mkd. T29S R6W S7 BT.

A maple, 12" diam., bears S.43½°E., 135 lks., mkd. T29 R6W S18 BT.

A fir, 16" diam., bears S.77°W., 142 lks., mkd. T29S R7W S13 BT.

A fir, 10" diam., bears N.61°W., 348 lks., mkd. T29S R7W S12 BT.

The corner falls in a ravine, drains NW.

BLM resurvey by Robert Chappel under Group #1616, surveyed June/Sept 1991 (DCSO records Vol. 50 Page(s) 18888)

Beginning at the cor. of secs. 7, 12, 13, and 18 on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set flush with the ground, with brass cap mkd.

T29S
 R7W R6W
 S 12 | S 7

 S 13 | S 18
 1957

from which the remaining bearing trees mkd. by Thielsen

A maple, 14 ins. diam., bears N. 80° E., 109 lks. dist., with scribe marks R6W S visible on partially healed blaze.

A maple, 16 ins. diam., bears S. 42½° E., 135 lks. dist., with illegible scribe marks visible on opened blaze. (Record, S. 43½° E.)

and new bearing trees

A fir, 8 ins. diam., bears S. 36½° W., 20½ lks. dist., mkd. T29S R7W S13 BT.

A madrone, 6 ins. diam., bears N. 10° W., 35 lks. dist., mkd. X BT.

The corner is located in small draw, drains N. 50° W.

continued next page

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7,18; 12 & 13 T29-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2270, Surveyed May/Aug. 2009 - (DCSO records Vol. 57 Page(s) 22726-7)

The cor. of secs. 7, 12, 13, & 18, on the W. bdy. of the Tp. monumented with an iron post, 2" dia., firmly set, projecting 1" above ground, with brass cap (properly) mkd. from which bearing trees mkd by Thielsen in 1957

A maple, 15" dia. bears N.80°E 71.9 ft., with no marks visible on a hollow, partially healed blaze.

A maple, 24" dia. bears S.42½°E., 89.1 ft., with scribe marks 7W Si visible on a partially opened blaze.

and bearing trees mkd Chappel

A fir, 16" dia., bears S.36½°W., 13.5 ft., with a healed blaze.

A madrone, 10" dia., bears N.10°W., 23.1 ft. with scribe marks BT visible on bark.

Corner is located at the intersection of broken down barbed and woven wire fences extending S & W in a shallow draw, drains N.40°W.

Fd BC & BTs per 2009 BLM survey, 1/2016 by G Lang; M170-41