

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 100540

PRIMARY CORNER DESCRIPTION 1/4 Cor. to Sec. 7; & Sec. 12 T29-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Pages 6453 and 6454)

Set 1/4 sec. post, from which:
A B. Oak, 15" diam., bears S.56°E, 98 lks.
A Laurel, 4" diam., bears S.55°W., 17 lks.

James W. Byron, Dep. Co. Surveyor - June 7, 1957 - C.S. 47/194

Found - Both original B.T's: The 15" B.O., S.56°E., (now 36" snag) shows old face and short sections of reverse scribe marks found near rotted area. 4" Laurel, S.55°W., (now 18") has been dozed out and is now laying 30 ft. down hill-shows old rotted face and possible faint scribe mks. Also found 2 fir stumps with good scribing, face to corner. A 12" Fir bears N.24½°W., 19.6 scribed 1/4 S 7 BT. A 12" Fir bears S.61°E., 12.8 ft. with good scribing. These trees scribed by Art Boyer about 30 yrs. ago states Geo. Voytilla, Not recorded. (See signed statement in file).
Set an iron pipe with brass cap at corner mkd:

Douglas County Surveyors Office
T29S
¼S S12 S 7
R7W R6W
1957

From which:
10" R. Fir, N.61°W., 101.6 ft., mkd. 1/4 S T29S R7W, CS BT
12" Laurel, S.80°W., (?) ft., mkd. 1/4 S T29S R7W, CS BT

BLM Resurvey by Hans W. Theilsen - under group #346 - Surveyed Aug 1959 (DCSO records Vol. 30 Pgs 12804 & 12805)

The ¼ sec. cor., perpetuated and recorded by the Co. Surveyor from the original bearing trees, monumented with an iron post, 1" diam., extending 8" above ground, firmly set, with brass cap mkd: County Surveyors Office

T29S
R R
7 ¼S 12 S 7 6
R7W R6W

From which:
A madrone, 12" diam., bears S.80°W., 109 lks., mkd. 1/4 S. T29S R7W CS BT.
A fir, 10" diam., bears N.61°W., 155 lks., mkd. 1/4 S. T29S R7W CS BT.

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 7; 12 T29-7

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Marvin C. Ramsey - Assistants: Paul E. Jonas; Floyd H. Brock-
For J.H. Baxter & Co. - May 23, 1963 - C.S. File 51/258; M
26-8

To the 1/4 Sec. Cor. of secs. 7 & 12, monumented and witnessed
as described by the County record, dated 1957. The bearing
trees have been fire killed and no other trees within limits.

BLM resurvey by Robert Chappel, under Group #1616, Surveyed
June/Sept. 1991 (DCSO records Vol. 50 Page(s) 18889-90)

The 1/4 sec. cor. of secs. 7 and 12, monumented with an iron
post, 1 in. diam., firmly set, projecting 7 ins. above the
ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T29S

1/4 S12 7

R7 R6
1957

from which the remains of the bearing tree mkd. by James W.
Byron, Deputy County Surveyor, in 1957

A fir snag, 12 ins. diam., bears N. 61° W., 154 lks.
dist., with healed blaze. (Record, 155 lks.)

and new bearing trees

A madrone, 11 ins. diam., bears S. 19 3/4° E., 52
lks. dist., mkd. 1/4 S7 BT.

A madrone, 13 ins. diam., bears N. 46 3/4° W., 12
lks. dist., mkd. 1/4 S12 BT.

From this point, the National Geodetic Survey triangulation
station, "TWO OAKS," bears N. 31° 41' 55" W., 89.185 chs.
dist., monumented with an iron post, 2 ins. diam., firmly
set, projecting 10 ins. above the ground, with a brass cap
mkd. TWO OAKS 1942.

BLM resurvey by Robert Chappel, under Group #1616, Surveyed
June/Sept. 1991 (DCSO records Vol. 50 Page(s) 18889-90)

The 1/4 sec. cor. of secs. 7 and 12, monumented with an iron
post, 1 in. diam., firmly set, projecting 7 ins. above the
ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T29S

(Cont. Next Page)

TOWNSHIP 29 RANGE 06 POINT IDENTIFIER # 100540

PRIMARY CORNER DESCRIPTION 1/4 Cor. to Sec. 7; & Sec. 12 T29-7

Alias	Description
Alias	Description
Alias	Description
Alias	Description

from which the remains of the bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1957

A fir snag, 12 ins. diam., bears N. 61° W., 154 lks. dist., with healed blaze. (Record, 155 lks.)

and new bearing trees

A madrone, 11 ins. diam., bears S. 19 3/4° E., 52 lks. dist., mkd. ¼ S7 BT.

A madrone, 13 ins. diam., bears N. 46 3/4° W., 12 lks. dist., mkd. ¼ S12 BT.

From this point, the National Geodetic Survey triangulation station, "TWO OAKS," bears N. 31° 41' 55" W., 89.185 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above the ground, with a brass cap mkd. TWO OAKS 1942.